

BOSS® 570, 571, 572 & 575 Coil Cleaners



DESCRIPTION

BOSS® 570 Condenser Coil Cleaner is an acid based condenser coil cleaner formulated with heavy duty foaming action to quickly clean and brighten aluminum finned coils. For professional use only. **BOSS® 570** is a clear pink liquid.

USE PROPER MIX RATIO:

Heavy Duty - dilute with 3 parts water (3:1)

Moderate Duty - dilute with 5 parts water (5:1)

Light Duty - dilute with 10 parts water (10:1)

Rinse thoroughly when finished

BOSS® 571 Evaporator Coil Cleaner is formulated to quickly dissolve grease, dirt and nicotine without attacking the metal coils. **BOSS® 571** is biodegradable and requires no rinsing. For professional use only. **BOSS® 571** is a clear green liquid.

USE PROPER MIX RATIO:

Heavy Duty - dilute with 1 part water (1:1)

Moderate Duty - dilute with 3 parts water (3:1)

Light Duty - dilute with 6 parts water (6:1)

BOSS® 572 Multi-Purpose Cleaner/Degreaser is a heavy duty detergent formulation ideal for all surfaces soiled with grease, oil and dirt including; evaporator coils, heating coils, window units, air filters and motors. Excellent for use in pressure washers. For professional use only. **BOSS® 572** is a clear yellow liquid.

USE PROPER MIX RATIO:

Heavy Duty - dilute with 1 parts water (1:1)

Moderate Duty - dilute with 3 parts water (3:1)

Light Duty - dilute with 10 parts water (10:1)

BOSS® 575 Biodegradable Alkaline Condenser Coil Cleaner is a non-acid high foaming, alkaline based condenser coil cleaner. It is formulated to quickly clean and brighten aluminum finned coils without the harmful effects of acid based cleaners. For professional use only. **BOSS® 575** is a clear tan liquid.

USE PROPER MIX RATIO:

Heavy Duty - dilute with 3 part water (3:1)

Moderate Duty - dilute with 6 parts water (6:1)

Light Duty - dilute with 10 parts water (10:1)

Rinse thoroughly when finished

HOW TO USE

BOSS® 570

1. Shut off system
2. Using an acid resistant sprayer, spray solution into coils from the BOTTOM up.
3. Wait 3-5 minutes, then rinse thoroughly with water.

BOSS® 571

1. Apply solution with an acid resistant sprayer.
2. To ensure cleaner reaches all parts of the coil, apply to intake side of the coil ONLY. Spray accessible coils and turn on air as soon as possible to distribute material to all parts of coil.
3. Apply to intake side of coil.

BOSS® 572

1. For heavy duty applications such as concrete or machinery, dilute with water using a 1:1 mix ratio.
2. For light to moderate applications such as fabric, carpet or electronic air filters, dilute with water using a 3:1 mix ratio.
3. For use in a pressure washer, dilute with water using a 10:1 mix ratio.

BOSS® 575

1. Shut off system
2. Using an acid resistant sprayer, spray solution into coils from the BOTTOM up.
3. Wait 3-5 minutes, then rinse thoroughly with water.

CAUTION

- Wash hands after use
- Do not allow to freeze
- Keep containers closed
- Use with adequate ventilation
- Do not take internally
- Keep out of reach of children

Protect yourself from corrosive burns. Always wear corrosive resistant goggles and gloves. In case of eye or skin contact, flush with water for 15 minutes. Seek medical attention immediately. In case of ingestion, do not induce vomiting. Seek medical attention immediately. See Material Safety Data Sheet for additional cautions.

SHIPPING LIMITATIONS

Truck shipments only.

PACKAGING

BOSS® 570, 571, 572 & 575 Coil Cleaners are available in 1 gallon plastic jugs, individually bagged, 4 per case.

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

The supplier warrants only that its products will meet its specifications. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. The users exclusive remedy and the suppliers sole liability is limited to refund of the purchase price or replacement of any product shown to be otherwise than as warranted. The supplier will not be liable for incidental or consequential damages of any kind.

Suggestions of uses should not be taken as inducements to infringe any patents.

MADE IN U.S.A.

BOSS® PRODUCTS

Accumetric, LLC
350 Ring Road
Elizabethtown, KY 42701
800-928-BOSS(2677)
270-769-3385 FAX 270-765-2412
www.accumetricinc.com