

ANTI-SEIZE & LUBRICATING COMPOUND PART NO. 49501

DESCRIPTION

Dynatex® Anti-Seize is a heavy-duty, economical industrial anti-seize and lubricating paste containing very finely divided metallic particles in a special no-melt petroleum base grease. *Dynatex® Anti-Seize* leaves a protective film that seals and protects metal parts even under the most extreme conditions of heat, pressure, steam and water exposure.

Color	Silver Grey
Base Oil	Petroleum
Thickener.....	Synthetic
Texture.....	Buttery

USES

Dynatex® Anti-Seize was designed as a preventative maintenance tool providing complete parts protection on threaded fittings and all metal surfaces subjected to harsh environments or high temperatures to +2000°F. *Dynatex® Anti-Seize* was formulated to fit a wide variety of marine, metalworking, automotive, oilfield, construction and farm equipment applications. A few such examples include:

- ◆ Threaded Fittings
- ◆ Winches
- ◆ Valve Shafts
- ◆ Casting Equipment
- ◆ Conveyors
- ◆ Rig Drives
- ◆ Sprockets & Chains
- ◆ Manifold Studs & Bolts
- ◆ Brake Cams & Pins
- ◆ Splines & Worm Gears

ADVANTAGES

Dynatex® Anti-Seize is not just another anti-seize/thread lubricant. Unlike conventional products on the market, the maximum blend of metallic solids has been homogenized into a specially designed petroleum base grease, which **does not** contain clay or soap base thickeners. This helps to provide a superior product that will not melt and run out after application. It also helps to reduce friction of metal surfaces and allows easy movement of threaded connections during assembly and disassembly, which makes for tighter make-ups.

Other advantages include:

- ◆ Protects to +2000°F
- ◆ Non-Melting
- ◆ Prevents Rust & Corrosion
- ◆ Extreme Pressure Lubricant
- ◆ Reduces Torque
- ◆ Prevents Carbon Fusion
- ◆ Chemical Resistant
- ◆ Excellent Lubricity
- ◆ Steam & Water Resistant
- ◆ Prevents Galling & Seizing

TYPICAL SPECIFICATIONS

TESTS	ASTM TEST METHOD	RESULTS
N.L.G.I. Grade	-----	1
Penetration		
Unworked	D-217	290
Worked		320
Base Oils Viscosity,		
SUS @ 100 ⁰ F	D-445	990
SUS @ 210 ⁰ F	D-445	66
Pour Point, ⁰ F	D-97	0
Flash Point ⁰ F	D-92	430
Dropping Point, ⁰ C (⁰ F)	D-566	None

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it the user's responsibility to determine suitable of use. Since the supplier cannot know all the uses, or the conditions of use to which there products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

The supplier warrants only that its products will meet its specifications. There is no use, nor any other express or implied warranty. The users exclusive remedy and the suppliers sole liability is limited to refund of the purchase price or replacement of any product when to be otherwise than as warranted. The supplier will not be liable for incidental or consequential damages of any kind.

Suggestions of uses should not be taken as inducements to infringe any patents.



350 Ring Road Elizabethtown, Kentucky 42701 USA (800) 999-2937 TEL (270) 769-5557 FAX (270) 769-6418
Outside U.S. TEL +1(270) 769-5557 FAX +1(270) 769-6418
Email: sales@dynatexinc.com Website: www.dynatexinc.com