

ANTI-SEIZE & LUBRICATING COMPOUND PART NO. 49576

TYPICAL PROPERTIES

Color.....	Silver Grey
Base Oil.....	Petroleum
Thickener	Synthetic
Texture	Buttery
N.L.G.I. Grade	1
Flash Point.....	430°F



DESCRIPTION

Dynatex® Anti-Seize is a heavy-duty, economical industrial anti-seize and lubricating paste containing very finely divided metallic particles in a special no-melt petroleum base grease. *Dynatex® Anti-Seize* leaves a protective film that seals and protects metal parts even under the most extreme conditions of heat, pressure, and steam and water exposure.

FEATURES

Dynatex® Anti-Seize is not just another anti-seize/thread lubricant. Unlike conventional products on the market, the maximum blend of metallic solids has been homogenized into a specially designed petroleum base grease, which **does not** contain clay or soap base thickeners. This helps to provide a superior product that will not melt and run out after application.

It also helps to reduce friction of metal surfaces and allows easy movement of threaded connections during assembly and disassembly, which makes for tighter make-ups.

Other advantages include:

- Protects to 2000°F
- Prevents carbon fusion
- Non-melting
- Chemical resistant
- Prevents rust & corrosion
- Excellent lubricity
- Extreme pressure lubricant
- Steam & water resistant
- Reduces torque
- Prevents galling & seizing

TYPICAL APPLICATIONS

Dynatex® Anti-Seize was designed as a preventative maintenance tool providing complete parts protection on threaded fittings and all metal surfaces subjected to harsh environments or high temperatures to 2000°F. *Dynatex® Anti-Seize* was formulated to fit a wide variety of marine, metalworking, automotive, oilfield, construction and farm equipment applications. A few such examples include:

- Threaded fittings
- Winches
- Valve shafts
- Casting equipment
- Conveyors
- Rig drives
- Sprockets & chains
- Manifold studs & bolts
- Brake cams & pins
- Splines & worn gears

STORAGE AND SHELF LIFE

Dynatex® Anti-Seize should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building. **Dynatex® Anti-Seize** has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

The supplier warrants only that its products will meet its specifications. There is no use, nor any other express or implied warranty. The user's exclusive remedy and the supplier's sole liability is limited to refund of the purchase price or replacement of any product when to be otherwise than as warranted. The supplier will not be liable for incidental or consequential damages of any kind.

Suggestions of uses should not be taken as inducements to infringe any patents.



Dynatex
350 Ring Road
Elizabethtown
Kentucky 42701 USA
(800) 999-2937
TEL (270) 769-5557
FAX (270) 769-6418
Outside U.S.
TEL +1(270) 769-5557
FAX +1(270) 769-6418

Accumetric Asia Pacific, LTD
18 Kitpanit Bldg. 5th Floor
#502 Patpong Road
Suriyawong, Bangrak
Bangkok, 10500 Thailand
TEL (662) 634-3060
FAX (662) 634-3066

Email: sales@dynatexinc.com
Website: www.dynatexinc.com