

NICKEL ANTI-SEIZE PART NO. 49584

TYPICAL SPECIFICATIONS

Physical State	Soft grease
Color	Dark silver
Grease Carrier	Semi-synthetic
Specific Gravity.....	1.18
Percent Volatile	None
N.L.G.I. Grade.....	1
Flash Point.....	425°F
Dropping Point	None



DESCRIPTION

Dynatex® Nickel Anti-Seize is a heavy-duty anti-seize and lubricating paste containing a balanced blend of pure nickel and graphite, homogenized into a semi-synthetic, non-melting, grease base. **Dynatex® Nickel Anti-Seize** does not contain any sulfur, lead, copper, halogens, or clay fillers.

Dynatex® Nickel Anti-Seize leaves a protective film that seals and protects metal parts, even under the most extreme condition of heat, corrosive, and acidic environments.

FEATURES

- Contains no lead or copper
- Protects to 2000°F
- Prevents galling and seizing
- Acid resistance
- Waterproof
- Prevents rust and corrosion
- Prevents carbon fusion
- Non-melting

TYPICAL APPLICATIONS

Dynatex® Nickel Anti-Seize was designed as a preventative maintenance tool to provide complete parts protection on threaded fittings and all metal surfaces subjected to harsh environments or high temperatures to 2000°F (1427°C). It is recommended for use in applications, which prohibit the presence of copper. **Dynatex® Nickel Anti-Seize** was formulated to fit a wide variety of applications found in chemical and petrochemical plants, steel mills, and power generating facilities. A few such examples include:

- Manifold Studs
- Pipe Fittings
- Heat Exchangers
- Furnace Hinges
- Tailpipe assemblies
- Burner Tips
- Casting Equipment
- Catalytic converter assemblies

NOTE: NOT FOR USE ON OXYGEN OR LPG LINES

STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **Dynatex® Nickel Anti-Seize** has a shelf life of 12 months from date of shipment.

In Countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

The supplier warrants only that its products will meet its specifications. There is no use, nor any other express or implied warranty. The user's exclusive remedy and the supplier's sole liability is limited to refund of the purchase price or replacement of any product when to be otherwise than as warranted. The supplier will not be liable for incidental or consequential damages of any kind.

Suggestions of uses should not be taken as inducements to infringe any patents.

Dynatex® A division of Accumetric, LLC

Dynatex
350 Ring Road
Elizabethtown
Kentucky 42701 USA
(800) 999-2937
TEL (270) 769-5557
FAX (270) 769-6418
Outside U.S.
TEL +1(270) 769-5557
FAX +1(270) 769-6418

Accumetric Asia Pacific, LTD
18 Kitpanit Bldg. 5th Floor
#502 Patpong Road
Suriyawong, Bangrak
Bangkok, 10500 Thailand
TEL (662) 634-3060
FAX (662) 634-3066

Email: sales@dynatexinc.com
Website: www.dynatexinc.com