MSDS Document

Product BOSS® 810 Non-Intumescent Latex Firestop Sealant

1. Chemical Product and Company Identification

Trade Name of this Product BOSS® 810 Non-Intumescent Latex Firestop SealantSynonyms:03415RD10, 03575RD01, 03637RD17, C39022RD

MSDS ID BOSS810 Manufacturer Accumetric, LLC 350 Ring Road Elizabethtown, KY 42701

 Phone Number

 (270) 769-3385

 Emergency Phone

 CHEMTREC (800) 424-9300

 Revision Date
 12/17/2009



Health:	0
Fire:	0
Reactivity:	0
Specific	

2. Composition and Information on Ingredients

Ingredient Calcium Carbonate	CAS Number 471-34-1	Weight % 30% - 60%	ACGIH TLV 10 mg/m3	PEL 5 mg/m3	STEL
Acrylic resin	Proprietary	10% - 30%			
Water	7732-18-5	5% - 15%	0		
Phthalate plasticizer	Proprietary	5% - 10%			
Distillates (petroleum), hydrotreated middle	64742-46-7	3% - Max	5 mg/m3	5 mg/m3	10 mg/m3

3. Hazard Identification

Primary Routes of Entry Inhalation, skin contact

Eye Contact Direct contact may cause moderate irritation.

Page 2 6 Print Rev. Date 12/17/2009 MSDS ID BOSS810 BOSS® 810 Non-Intumescent Latex Firestop Sealant

Skin Contact

No evidence of adverse effects from available information.

Inhalation

Trace component and residual monomer may cause headache, nausea, and irritation of the nose, throat, and lungs in poorly ventilated areas.

Ingestion

No significant effects expected from a single short term exposure.

Health Hazards

The principle volatile component is water. Minor volatile components from the emulsion may cause headache and nausea. Prolonged and repeated skin contact can cause irritation. Treatment of overexposure should be directed at the control of symptoms and clinical condition.

Existing Conditions Aggravated by Exposure

No known applicable information.

4. First Aid Information

Eye Contact

Immediately flush with large amounts of water. If irritation occurs, seek medical attention.

Skin Contact

Wash affected area with soap and water.

Inhalation

Remove to fresh air. No first aid should be needed.

Ingestion

No harmful effects expected.

5. Fire Fighting Measures

Flash Point

Not determined

Flammability Limits in Air Lower: 0.9% by volume Upper: 15.3% by volume

Extinguishing Media

Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

Special Fire Fighting Procedures

Non-flammable (aqueous emulsion). After water evaporates, remaining material will burn. Breathing apparatus required when fighting fires in enclosed areas.

Unusual Fire or Explosion Hazards

Product will not burn, but may splatter if temperature exceeds boiling point of water. Dried

Page 3 6 Print Rev. Date 12/17/2009 MSDS ID BOSS810 BOSS® 810 Non-Intumescent Latex Firestop Sealant

solids can burn, giving off oxides of carbon.

Flammability: TDGR Class Sensitivity to impact Sensitivity to static discharge

6. Accidental Release Measures

Steps to be taken in case of spill or release

Restrict area to only those personnel needed. Major spills should be collected for disposal. Minor spills may be flushed to sewer if permitted by state, federal and local regulations.

7. Handling and Storage

Handling

Avoid breathing vapors in top of shipping container. Keep container closed. Use with adequate ventilation. Avoid contact with skin and clothing. Wash throughly after handling.

Storage

Store in a cool dry place. Protect from freezing and excessive heat.

8. Exposure Controls and Personal Protection

Eye Protection

Wear safety glasses with side shields. Eyewash fountains should be readily available.

Skin Protection

Impervious gloves are suggested.

Ventilation

Good general ventilation should be sufficient.

Respiratory Protection

If engineering controls do not maintain airborne concentrations of hazardous ingredients below TLV, then a NIOSH/MSHA approved organic vapor respirator should be used. Not required under normal usage and adequate ventilation.

9. Physical and Chemical Properties

Physical State	Paste
Specific Gravity	1.624846
Density Ibs/Gal.	13.56
Color/Appearance	Colored paste
Odor	Slight
рН	7.85
Boiling/Cond. Point	100C
Melting/Freezing Point	0C
Solubility	Dilutable in wet stage
Evaporation Rate	Slower than n-Butyl Acetate
VOC %	15.5 g/L

Page 4 6 Print Rev. Date 12/17/2009 MSDS ID BOSS810 BOSS® 810 Non-Intumescent Latex Firestop Sealant

Percent Volatile	19%
Viscosity	750,000 cPs
Vapor Density	Lighter than air
Vapor Pressure	Not Determined

Note

The above information is not intended for use in preparing product specifications. Contact Accumetric LLC before writing specifications.

10. Stability and Reactivity

Chemical Stability Stable

Hazardous Polymerization Will not occur

Materials to Avoid / Incompatibility None known

Conditions to Avoid None known

11. Toxicological Information

Component Toxicology Information No known applicable information.

Special Hazard Information on Components

No known applicable information.

12. Ecological Information

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

Environmental Fate and Distribution

Complete information is not yet available.

13. Disposal Considerations

Waste Disposal Method

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Page 5 6 Print Rev. Date 12/17/2009 MSDS ID BOSS810 BOSS® 810 Non-Intumescent Latex Firestop Sealant

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

14. Transportation Information

DOT Road Shipment Information Not subject to DOT.

Air Shipment (IATA) Not subject to IATA regulations.

Ocean Shipment (IMDG)

Not subject to IMDG code.

15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status

All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

California Proposition 65

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known

SARA Title III Section 302 Extremely Hazardous Substances None

SARA Title III Section 304 CERCLA Hazardous Substances None

SARA Title III Section 313 Toxic Chemicals None present or none present in regulated quantities.

Massachusetts Mineral Spirits (8052-41-3)

New Jersey Mineral Spirits (8052-41-3)

Pennsylvania Mineral Spirits (8052-41-3)

Page 6 6 Print Rev. Date 12/17/2009 MSDS ID BOSS810 BOSS® 810 Non-Intumescent Latex Firestop Sealant

16. Other Information

Disclaimer

The data contained herein is based upon information that Accumetric LLC believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements to suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.