# **MSDS Document**

# Product BOSS® 180 Multi-Seal Insulation Anchor Pin System Adhesive

# **1. Chemical Product and Company Identification**

Product BOSS® 180 Multi-Seal Insulation Anchor Pin System Adhesive

**Synonyms:** 04224WH10, 04224WH25, C04072WH

# MSDS ID BOSS180 Manufacturer

Accumetric, LLC 350 Ring Road Elizabethtown, KY 42701



 Phone Number

 (270) 769-3385

 Emergency Phone

 CHEMTREC (800) 424-9300

 CHEMTREC International (703) 527-3887

 Revision Date
 10/14/2013

Health:	1
Fire:	1
Reactivity:	0
Stock	

# 2. Composition and Information on Ingredients

Ingredient Calcium carbonate	CAS Number 1317-65-3	<b>Weight %</b> 25% - 50%	ACGIH TI 10 mg/m3
Amorphous fumed silica	112945-52-5	4% - 10%	10 mg/m3
Vinyl Oximino Silane	2224-33-1	5% - Max	
Methyl Oximino Silane	22984-54-9	5% - Max	
Gamma-aminopropyl triethoxysilane	919-30-2	3% - Max	

<b>ACGIH TLV</b> 10 mg/m3	<b>PEL</b> 5 mg/m3	STEL
10 mg/m3	6 mg/m3	

Page 2 of 7 Print Rev. Date 10/14/2013 MSDS ID BOSS180 BOSS® 180 Multi-Seal Insulation Anchor Pin System Adhesive

# 3. Hazard Identification

# **Eye Contact**

Direct eye contact irritates slightly with redness and swelling.

# **Skin Contact**

A single short term exposure (less than 24 hours) may irritate. Repeated prolonged contact (24 to 48 hours) may irritate moderately. Product contains oximes which are possible skin sensitizers.

# Inhalation

Vapor overexposure may cause drowsiness, injure blood, liver and may irritate eyes, nose, and throat.

# Ingestion

Small amounts transferred to the mouth by fingers during use, etc., should not injure. Swallowing large amounts may injure slightly.

# **Existing Conditions Aggravated by Exposure**

No known applicable information.

# Comment

Methyl ethyl ketoxime (MEKO) is formed upon contact with water or humid air. Male rodents exposed to MEKO vapor throughout their lifetime developed liver tumors. Since many commonly used chemicals cause liver tumors in rats and mice, additional testing is planned by the MEKO supplier to determine any relevance to humans. Until more data is known, exposure levels should be maintained as low as possible.

# Note

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

# 4. First Aid Information

# **Eye Contact**

Immediately flush with water for 15 minutes.

# **Skin Contact**

Remove from skin and immediately flush with water for 15 minutes. Get medical attention if irritation or ill effects develop or persist.

# Inhalation

Remove to fresh air. If symptoms persist, obtain appropriate medical attention.

# Ingestion

Get medical attention.

# Comments

Treat according to person's condition and specifics of exposure.

Page 3 of 7 Print Rev. Date 10/14/2013 MSDS ID BOSS180 BOSS® 180 Multi-Seal Insulation Anchor Pin System Adhesive

# 5. Fire Fighting Measures

**Flash Point** 

Not applicable

Auto-ignition Temperature Not determined

Flammability Limits in Air Not determined

# **Extinguishing Media**

On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.

# **Special Fire Fighting Procedures**

Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

# **Unusual Fire or Explosion Hazards**

None known

# 6. Accidental Release Measures

# Steps to be taken in case of spill or release

Observe all personal protection equipment. Use absorbent material to collect and contain material for disposal.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

# 7. Handling and Storage

# Handling

Avoid breathing vapors in top of shipping container. Keep container closed. Use with adequate ventilation. Avoid contact with skin and clothing. Wash throughly after handling.

# Storage

Keep container closed and store in a cool, well ventilated area, away from water or moisture.

# 8. Exposure Controls and Personal Protection

# **Component Exposure Limits**

Methyl ethyl ketoxime is formed upon contact with water or moisture in the air. Provide

Page 4 of 7 Print Rev. Date 10/14/2013 MSDS ID BOSS180 BOSS® 180 Multi-Seal Insulation Anchor Pin System Adhesive

adequate ventilation to control exposures to within the exposure guideline of 2 ppm (TWA).

# **Engineering Controls**

Local Ventilation: Recommended General Ventilation: Recommended

# **Eye Protection**

Use proper protection - safety glasses as a minimum.

#### **Skin Protection**

Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and throughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves: Silver Shield® 4H®

#### **Respiratory Protection**

Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.

#### Suitable Respirator:

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits as determined by air sampling or are unknown, appropriate respiratory protection should be worn. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

# Comment

Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control methyl ethyl ketoxime within the exposure guidelines or use respiratory protection.

# 9. Physical and Chemical Properties

Physical State	Paste
Specific Gravity	1.3
Color/Appearance	Various
Odor	Slight
Boiling/Cond. Point	Not determined
Melting/Freezing Point	Not determined
Solubility	Dilutable in wet stage
Evaporation Rate	Not determined
VOC %	47 g/L
Vapor Density	Not determined
Vapor Pressure	Not determined

#### Note

The above information is not intended for use in preparing product specifications. Contact Accumetric LLC before writing specifications.

Page 5 of 7 Print Rev. Date 10/14/2013 MSDS ID BOSS180 BOSS® 180 Multi-Seal Insulation Anchor Pin System Adhesive

# 10. Stability and Reactivity

Hazardous Polymerization Will not occur

Materials to Avoid / Incompatibility Oxidizing material can cause a reaction.

Chemical Stability Stable

Conditions to Avoid None known

# **11. Toxicological Information**

# **Special Hazard Information on Component**

Methyl Oximino Silane (22984-54-9) Possible skin sensitizer Vinyl Oximino Silane (2224-33-1) Possible skin sensitizer

# **Component Toxicology Information**

Methyl ethyl Ketoxime (MEKO) is formed upon contact with water or humid air. Male rodents exposed to MEKO vapor throughout their lifetime developed liver tumors. Since many commonly used chemicals cause liver tumors in rats and mice, additional testing is planned by the MEKO supplier to determine any relevance to humans. Until more data is known, exposure levels should be maintained as low as achievable.

# Carcinogenicity

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

**Mutagenicity** This product is not known to be a mutagen.

# Teratogenicidad

No se tiene conocimiento de que este producto sea teratógeno.

# **Reproductive Toxin**

This product is not known to be a reproductive toxin.

# **12. Ecological Information**

# **Environmental Effects**

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

# **Environmental Fate and Distribution**

Complete information is not yet available.

Page 6 of 7 Print Rev. Date 10/14/2013 MSDS ID BOSS180 BOSS® 180 Multi-Seal Insulation Anchor Pin System Adhesive

# **13. Disposal Considerations**

# Waste Disposal Method

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

# 14. Transportation Information

# DOT Road Shipment Information

DOT(USA): Caulking & Glaziers, NOI DOT Hazard Classification: None UN/NA Number: Not applicable Label Required: None Marine Pollutant: None

# **Ocean Shipment (IMDG)**

Not subject to IMDG code.

# **15. Regulatory Information**

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

# **TSCA Status**

All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

SARA Title III Section 302 Extremely Hazardous Substances None

SARA Titre III Section 304 CERCLA Substances dangereuses None

# SARA Title III Section 312 Hazard Class

Acute: Yes Chronic: Yes Fire: No Pressure: No Reactive: No

SARA Title III Section 313 Toxic Chemicals None present or none present in regulated quantities.

Page 7 of 7 Print Rev. Date 10/14/2013 MSDS ID BOSS180 BOSS® 180 Multi-Seal Insulation Anchor Pin System Adhesive

# **California Proposition 65**

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known

# Massachusetts

Silica, amorphous fumed (112945-52-5)

# **New Jersey**

Silica, amorphous (112945-52-5) Dimethyl siloxane, hydroxy-terminated (70131-67-8) Polydimethylsiloxane (63148-62-9) Methyl tri (ethylmethylketoxime) silane (22984-54-9) Calcium carbonate, treated (1317-65-3) Vinyl oximino silane (2224-33-1)

# Pennsylvania

Silica, amorphous (112945-52-5) Dimethyl siloxane, hydroxy-terminated (70131-67-8) Polydimethylsiloxane (63148-62-9) Methyl tri (ethylmethylketoxime) silane (22984-54-9) Calcium carbonate, treated (1317-65-3) Vinyl oximino silane (2224-33-1)

# Canada Domestic Substances List

All ingredients are listed on the DSL.

# **16. Other Information**

# Disclaimer

The data contained herein is based upon information that Accumetric LLC believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.