MSDS Document

Product BOSS® 503 Nickel Anti-Seize Compound

1. Chemical Product and Company Identification

Trade Name of this Product BOSS® 503 Nickel Anti-Seize Compound

Synonyms: 02070NK10, 02068NK10

MSDS ID BOSS503

Manufacturer Accumetric, LLC 350 Ring Road Elizabethtown, KY 42701 Phone Number
(270) 769-3385

Emergency Phone
CHEMTREC (800) 424-9300

Revision Date 12/17/2009



2. Composition and Information on Ingredients

Ingredient NJTSRN 80100362-5008P	CAS Number Trade Secret	Weight % 60% - 70%	ACGIH TLV	PEL	STEL
Nickel, as fume or dust	7440-02-0	15% - 20%	1.5 mg/m	1 mg/m	
Graphite powder	7782-42-5	15% - 20%	2.0 mg/m3	2.5 mg/m3	
Aluminum	7429-90-5	1% - 5%	10 mg/m3	5 mg/m3	
NJTSRN 80100362-5004P	Trade Secret	1% - 5%			
NJTSRN 80100362-5014P	Trade Secret	0.5% - 1%			
NJTSRN 80100362-5002P	Trade Secret	0.1% - 0.5%			

Page 2 5 Print Rev. Date 12/17/2009 MSDS ID BOSS503 BOSS® 503 Nickel Anti-Seize Compound

3. Hazard Identification

Symptoms of Overexposure

May cause irritation to eyes and skin on sensitive individuals.

Existing Conditions Aggravated by Exposure

Prolonged or repeated contact may produce mild skin irritation and inflammation. Personnel with pre-existing skin disorder should avoid contact.

4. First Aid Information

Eye Contact

Immediately flush eyes with water for at least 15 minutes. Get medical attention if irritation develops.

Skin Contact

Wash with soap and water. If irritation occurs, seek medical attention.

Inhalation

Remove to fresh air. If symptoms persist, obtain appropriate medical attention.

Ingestion

Do not induce vomiting. Keep calm. Obtain medical attention.

5. Fire Fighting Measures

Flash Point 400F FP Method COC

Extinguishing Media

Carbon Dioxide, Dry Chemical, Foam

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products:

Carbon Dioxide

Carbon Monoxide

Trace metal oxides

Special Fire Fighting Procedures

Fight like a fuel oil fire. Cool fire exposed containers with water spray. Use water to keep fire exposed containers cool to prevent pressure build-up. Fire fighter should wear OSHA/NIOSH approved self-contained breathing apparatus.

Unusual Fire or Explosion Hazards

None known

6. Accidental Release Measures

Steps to be taken in case of spill or release

Stop flow, scrape, wipe, mop up or absorb with diatomaceous earth or other inert material.

Page 3 5 Print Rev. Date 12/17/2009 MSDS ID BOSS503 BOSS® 503 Nickel Anti-Seize Compound

Disposal should be in accordance with local, state, and federal regulations.

7. Handling and Storage

Handling

Spills may cause slippery floors. Proper footwear required. Remove contaminated clothing and launder before reuse. Wash hands with soap and water before eating, drinking or smoking. Discard contaminated leather gloves and shoes.

Storage

Avoid storage near open flame or other sources of ignition.

8. Exposure Controls and Personal Protection

Eye Protection

Safety goggles or glasses with side shields are recommended.

Skin Protection

Use neoprene or nitrile rubber gloves to prevent skin contact.

Respiratory Protection

No special requirements under ordinary conditions of use and with adequate ventilation.

Other Protective Clothing or Equipment

None under normal use; however, use of solvent resistant aprons or other clothing is recommended. Use of chemically resistant boots is recommended.

Other Precautions

Have emergency shower and eye wash available.

9. Physical and Chemical Properties

Physical State Soft grease Specific Gravity 1.18 Color/Appearance Dark silver Odor Petroleum odor Boiling/Cond. Point Not applicable Melting/Freezing Point Not applicable Solubility Insoluble in water **Evaporation Rate** Not applicable Percent Volatile None Vapor Density Not applicable

Vapor Pressure Not applicable

Note

The above information is not intended for use in preparing product specifications. Contact Accumetric LLC before writing specifications.

10. Stability and Reactivity

Chemical Stability

Stable

Page 4 5 Print Rev. Date 12/17/2009 MSDS ID BOSS503 BOSS® 503 Nickel Anti-Seize Compound

Hazardous Polymerization

Will not occur

Materials to Avoid / Incompatibilities

Keep away from strong oxidizing agents.

Conditions to Avoid

Do not heat above flash point. Do not weld.

11. Toxicological Information

Carcinogens

IARC concluded that powdered Metallic Nickel is possibly carcinogenic to humans. Not carcinogenic by ingestion. (NIOSHA U.S.F.D.A.-GRAS)

12. Ecological Information

Environmental Fate and Distribution

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

13. Disposal Considerations

Waste Disposal Method

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations, but contains SARA regulated substances. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

14. Transportation Information

15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Page 5 5 Print Rev. Date 12/17/2009 MSDS ID BOSS503 BOSS® 503 Nickel Anti-Seize Compound

TSCA Status

All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

SARA Title III Section 302 Extremely Hazardous Substances None

SARA Title III Section 304 CERCLA Hazardous Substances Nickel Powder (7440-02-0)

SARA Title III Section 313 Toxic Chemicals

Nickel Powder (7440-02-0) Aluminum Powder (7429-90-5)

California Proposition 65

Nickel Powder (7440-02-0)

New Jersey

Nickel Powder (7440-02-0) Aluminum Powder (7429-90-5)

Pennsylvania

Graphite Powder (7782-42-5) Nickel Powder (7440-02-0) Aluminum Powder (7429-90-5)

16. Other Information

Disclaimer

The data contained herein is based upon information that Accumetric LLC believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements to suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.