MSDS Document

Product BOSS® 826 Acoustical Sound Sealant

1. Chemical Product and Company Identification

Trade Name of this Product BOSS® 826 Acoustical Sound Sealant

Synonyms: 03901WH10, 03902WH01

MSDS ID BOSS826


Manufacturer
Accumetric, LLC
350 Ring Road

Elizabethtown, KY 42701

Phone Number (270) 769-3385 Emergency Phone

CHEMTREC (800) 424-9300 **Revision Date** 12/17/2009





2. Composition and Information on Ingredients

Ingredient Calcium Carbonate	CAS Number 471-34-1	Weight % 35% - 65%	ACGIH TLV 10 mg/m3	PEL 5 mg/m3	STEL
Vinyl acetate/acrylic copolymer	Proprietary	10% - 30%			
Phthalate plasticizer	Proprietary	1% - 5%			
Distillates (petroleum), hydrotreated middle	64742-46-7	1% - Max	5 mg/m3	5 mg/m3	10 mg/m3

3. Hazard Identification

Primary Routes of Entry

Inhalation, skin contact

Inhalation

Trace component and residual monomer may cause headache, nausea, and irritation of the

Page 2 6 Print Rev. Date 12/17/2009 MSDS ID BOSS826 BOSS® 826 Acoustical Sound Sealant

nose, throat, and lungs in poorly ventilated areas.

Skin Contact

No significant effects expected from a single short-term exposure.

Eye Contact

Direct contact may cause moderate irritation.

Ingestion

No significant effects expected from a single short term exposure.

Health Hazards

The principle volatile component is water. Minor volatile components from the emulsion may cause headache and nausea. Prolonged and repeated skin contact can cause irritation. Treatment of overexposure should be directed at the control of symptoms and clinical condition.

4. First Aid Information

Eye Contact

Flush with warm water for several minutes. Obtain medical attention.

Inhalation

Remove to fresh air. If symptoms persist, obtain appropriate medical attention.

Skin Contact

Wash affected area with soap and water.

Ingestion

No first aid should be needed.

5. Fire Fighting Measures

Flash Point Not determined

Flammability Limits in Air

Lower: 0.9% by volume Upper: 15.3% by volume

Extinguishing Media

Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

Special Fire Fighting Procedures

Non-flammable (aqueous emulsion). After water evaporates, remaining material will burn. Breathing apparatus required when fighting fires in enclosed areas.

Unusual Fire or Explosion Hazards

Product will not burn, but may splatter if temperature exceeds boiling point of water. Dried solids can burn, giving off oxides of carbon.

Page 3 6 Print Rev. Date 12/17/2009 MSDS ID BOSS826 BOSS® 826 Acoustical Sound Sealant

Flammability: TDGR Class

Sensitivity to impact

Sensitivity to static discharge

6. Accidental Release Measures

Steps to be taken in case of spill or release

Restrict area to only those personnel needed. Major spills should be collected for disposal. Minor spills may be flushed to sewer if permitted by state, federal and local regulations.

7. Handling and Storage

Handling

Avoid breathing vapors in top of shipping container. Keep container closed. Use with adequate ventilation. Avoid contact with skin and clothing. Wash throughly after handling.

Storage

Store in a cool dry place. Protect from freezing and excessive heat.

8. Exposure Controls and Personal Protection

Ventilation

Local exhaust ventilation is recommended to maintain vapor level below TLV.

Respiratory Protection

No respiratory protection should be needed with good local ventilation.

Eye Protection

Safety goggles or glasses with side shields are recommended.

Skin Protection

Impervious gloves are suggested.

9. Physical and Chemical Properties

Physical State Paste
Specific Gravity 1.72
Density Ibs/Gal. 14.3541
Color/Appearance Various
Odor Slight
pH 8
Boiling/Cond. Point 100C
Melting/Freezing Point 0C

Solubility Dilutable in wet stage
Evaporation Rate Slower than n-Butyl Acetate

VOC % 8.6 g/L
Percent Volatile 30%
Viscosity 750,000 cPs
Vapor Density Lighter than air
Vapor Pressure Not Determined

Page 4 6 Print Rev. Date 12/17/2009 MSDS ID BOSS826 BOSS® 826 Acoustical Sound Sealant

Note

The above information is not intended for use in preparing product specifications. Contact Accumetric LLC before writing specifications.

10. Stability and Reactivity

Chemical Stability

Stable

Materials to Avoid / Incompatibility

None known

Hazardous Polymerization

Will not occur

11. Toxicological Information

Component Toxicology Information

No known applicable information.

Special Hazard Information on Components

No known applicable information.

12. Ecological Information

Environmental Fate and Distribution

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

13. Disposal Considerations

Waste Disposal Method

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Page 5 6 Print Rev. Date 12/17/2009 MSDS ID BOSS826 BOSS® 826 Acoustical Sound Sealant

14. Transportation Information

DOT Road Shipment Information

Not subject to DOT.

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status

All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

SARA Title III Section 302 Extremely Hazardous Substances

None

SARA Title III Section 304 CERCLA Hazardous Substances

None

SARA Title III Section 312 Hazard Class

Acute: Yes Chronic: No Fire: No Pressure: No Reactive: No

SARA Title III Section 313 Toxic Chemicals

None present or none present in regulated quantities.

California Proposition 65

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:

None known

16. Other Information

Disclaimer

The data contained herein is based upon information that Accumetric LLC believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements to suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with

Page 6 6 Print Rev. Date 12/17/2009 MSDS ID BOSS826 BOSS® 826 Acoustical Sound Sealant

the use of the material or the results to be obtained from the use thereof.