

MSDS Document

Product BOSS® 9222-5 Screw Locking Compound

1. Chemical Product and Company Identification

Trade Name of this Product BOSS® 9222-5 Screw Locking Compound

Synonyms: 04256PU09

MSDS ID BOSS9222-5

Manufacturer

Accumetric, LLC
350 Ring Road
Elizabethtown, KY 42701


Phone Number

(270) 769-3385

Emergency Phone

CHEMTREC (800) 424-9300

Revision Date 7/24/2012



Health:	1
Fire:	1
Reactivity:	1
Specific	

2. Composition and Information on Ingredients

Ingredient	CAS Number	Weight %	ACGIH TLV	PEL	STEL
Dimethacrylate Ester	25852-47-5	65% - 75%			
Cumene Hydroperoxide	80-15-9	1% - 3%	1 ppm Skin	None	
Amorphous fumed silica	112945-52-5	0.1% - 1%	10 mg/m3	6 mg/m3	

3. Hazard Identification

Toxicity

Mild eye irritant

Primary Routes of Entry

Eye contact, skin contact, inhalation

Symptoms of Exposure

May cause dermatitis with prolonged contact on sensitive individuals. May cause

respiratory tract irritation.

Existing Conditions Aggravated by Exposure

Eye, skin and respiratory disorders.

4. First Aid Information

Eye Contact

Flush with warm water for 15 minutes. Obtain medical attention.

Skin Contact

Wash affected area with soap and water. Remove contaminated clothing and shoes.

Ingestion

Do not induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation

Remove to fresh air. If symptoms persist, obtain appropriate medical attention.

5. Fire Fighting Measures

Flash Point Greater than 93°F
FP Method TCC

Extinguishing Media

Carbon Dioxide, Dry Chemical, Foam

Special Fire Fighting Procedures

None

Unusual Fire or Explosion Hazards

None known

Hazardous Products Formed by Fire or Thermal Decomposition

Irritating organic vapors; oxides of carbon, sulfur and nitrogen.

6. Accidental Release Measures

Steps to be taken in case of spill or release

Observe all personal protection equipment recommendations. Soak up with inert absorbent. Store in a partly filled, closed container until disposal. Prevent product from entering drains. Local, state and federal regulations may apply to releases and disposal of this material, as well as those materials and items employed in cleanup of releases.

7. Handling and Storage

Handling

Avoid contact with skin, eyes, and clothing. Avoid breathing vapor or mist.

Storage

Store at or below 100F. Keep away from heat, sparks and open flames.

8. Exposure Controls and Personal Protection

Eye Protection

Safety goggles or glasses with side shields are recommended.

Skin Protection

Rubber, polyethylene, or neoprene gloves.

Ventilation

Local exhaust ventilation is recommended to maintain vapor level below exposure limits.

Respiratory Protection

Use NIOSH approved respirator for individuals who are sensitive.

Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions. For further information regarding aerosol inhalation toxicity, please refer to the guidance document regarding the use of silicone-based materials in aerosol applications that has been developed by the silicone industry (www.SEHSC.com).

9. Physical and Chemical Properties

Physical State	Liquid
Specific Gravity	1.1
Color/Appearance	Purple
Odor	Mild
Boiling/Cond. Point	Greater than 300°F
Solubility	Slight in water
Evaporation Rate	Not Applicable
VOC %	0.665%, 6.53 g/L EPA method
Vapor Density	Approximately 3 (air = 1)
Vapor Pressure	Less than 5mm Hg @ 200°F

Note

The above information is not intended for use in preparing product specifications. Contact Accumetric LLC before writing specifications.

10. Stability and Reactivity

Chemical Stability

Stable

Hazardous Polymerization

Will not occur

Chemical Incompatibilities

Strong oxidizers

Hazardous Decomposition Products

Oxides of carbon, sulfur, and nitrogen

11. Toxicological Information

NIOSH - Selected LD50s and LC50s

Acute oral LD50: >10,000 mg/kg (rat)

Acute dermal LD50: >5,000 mg/kg (rabbit)

12. Ecological Information

Environmental Fate and Distribution

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

13. Disposal Considerations

Waste Disposal Method

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

14. Transportation Information

Voie terrestre DOT

Pas assujetti au DOT

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR

1910.1200.

TSCA Status

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

California Proposition 65

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:

None known

SARA Title III Section 313 Toxic Chemicals

Cumene Hydroperoxide (80-15-9)

16. Other Information

Disclaimer

The data contained herein is based upon information that Accumetric LLC believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.