MSDS Document

Product BOSS® 9290-5 Wicking Compound

1. Chemical Product and Company Identification

Trade Name of this Product BOSS® 9290-5 Wicking CompoundSynonyms:04255GN09

MSDS ID BOSS9290-5 Manufacturer Accumetric, LLC 350 Ring Road Elizabethtown, KY 42701


 Phone Number

 (270) 769-3385

 Emergency Phone

 CHEMTREC (800) 424-9300

 Revision Date
 7/24/2012



Health:	1
Fire:	1
Reactivity:	1
Specific	

2. Composition and Information on Ingredients

Ingredient Dimethacrylate Ester	CAS Number 25852-47-5	Weight % 65% - 75%	ACGIH TLV	PEL	STEL
Bisphenol A Fumurate Resin	39382-25-7	20% - 30%			
Cumene Hydroperoxide	80-15-9	1% - 3%	1 ppm Skin	None	
Polyethylene, homopolymer	9002-88-4	1% - 3%			
Saccharin	81-07-2	1% - 3%			
Dyes	Trade Secret	0.1% - 1%			
Organic Acid	Trade Secret	0.1% - 1%			
Amorphous fumed silica	112945-52-5	0.1% - 1%	10 mg/m3	6 mg/m3	

Page 2 6 Print Rev. Date 07/24/2012 MSDS ID BOSS9290-5 BOSS® 9290-5 Wicking Compound

3. Hazard Identification

Primary Routes of Entry

Eye contact, skin contact.

Eye Contact Mild eye irritant

Symptoms of Overexposure

May cause dermatitis with prolonged contact on sensitive individuals.

Existing Conditions Aggravated by Exposure

No known applicable information.

4. First Aid Information

Ingestion Do not induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation

Not known to cause inhalation problems.

Skin Contact

Wash affected area with soap and water.

Eye Contact

Rinse with water for 15 minutes. Obtain medical attention.

5. Fire Fighting Measures

Flash Point	> 200°F
FP Method	Tag Closed Cup

Extinguishing Media Carbon Dioxide, Dry Chemical, Foam

Unusual Fire or Explosion Hazards None known

Special Fire Fighting Procedures None

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Irritating organic vapors

6. Accidental Release Measures

Steps to be taken in case of spill or release

Observe all personal protection equipment recommendations. Soak up with inert absorbent.

Page 3 6 Print Rev. Date 07/24/2012 MSDS ID BOSS9290-5 BOSS® 9290-5 Wicking Compound

Store in a partly filled, closed container until disposal. Prevent product from entering drains. Local, state and federal regulations may apply to releases and disposal of this material, as well as those materials and items employed in cleanup of releases.

7. Handling and Storage

Storage

Store below 100°F.

Handling

Avoid contact with skin and eyes.

8. Exposure Controls and Personal Protection

Skin Protection

Rubber, polyethylene, or neoprene gloves.

Eye Protection

Safety goggles or glasses with side shields are recommended.

Ventilation

Does not apply.

Respiratory Protection

Does not apply.

Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions. For further information regarding aerosol inhalation toxicity, please refer to the guidance document regarding the use of silicone-based materials in aerosol applications that has been developed by the silicone industry (www.SEHSC.com).

9. Physical and Chemical Properties

Physical State	Liquid
Specific Gravity	1.07
Color/Appearance	Green
Odor	Mild
Boiling/Cond. Point	Greater than 300°F
Solubility	Negligible
Evaporation Rate	Not Applicable
Vapor Density	Approxiamtely 3 (air = 1)
Vapor Pressure	Less than 5mm Hg @ 200°F

Note

The above information is not intended for use in preparing product specifications. Contact Accumetric LLC before writing specifications.

10. Stability and Reactivity

Chemical Stability Stable

Page 4 6 Print Rev. Date 07/24/2012 MSDS ID BOSS9290-5 BOSS® 9290-5 Wicking Compound

Hazardous Polymerization Will not occur

Conditions to Avoid None known

Materials to Avoid / Incompatibility Strong oxidizers, free radical initiators, inert gases

11. Toxicological Information

Component Toxicology Information No known applicable information.

Special Hazard Information on Components No known applicable information.

12. Ecological Information

Environmental Fate and Distribution Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

13. Disposal Considerations

Waste Disposal Method

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

14. Transportation Information

Voie terrestre DOT Pas assujetti au DOT

Ocean Shipment (IMDG) Not subject to IMDG code.

Page 5 6 Print Rev. Date 07/24/2012 MSDS ID BOSS9290-5 BOSS® 9290-5 Wicking Compound

Air Shipment (IATA) Not subject to IATA regulations.

15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status

All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

SARA Title III Section 302 Extremely Hazardous Substances None

SARA Titre III Section 304 CERCLA Substances dangereuses None

SARA Title III Section 312 Hazard Class

Acute: Yes Chronic: No Fire: No Pressure: No Reactive: No

SARA Title III Section 313 Toxic Chemicals

Cumene Hydroperoxide (80-15-9)

California Proposition 65

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: Saccharin. Proper usage necessitates no Proposition 65 warning.

New Jersey

Cumene hydroperoxide (80-15-9) Saccharin (81-07-2)

Pennsylvania

Cumene hydroperoxide (80-15-9) Saccharin (81-07-2)

16. Other Information

Disclaimer

The data contained herein is based upon information that Accumetric LLC believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty,

Page 6 6 Print Rev. Date 07/24/2012 MSDS ID BOSS9290-5 BOSS® 9290-5 Wicking Compound

expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.