

Accumetric, LLC 350 Ring Road Elizabethtown, KY 42701 800-928-BOSS(2677) 270-769-3385 FAX 270-765-2412

This Safety Data Sheet packet contains the SDS for the products listed below:

BOSS® MultiSeal 125 BOSS® MultiSeal 125 Translucent

These two products have different formulations. Please confirm that you have the proper SDS for the product being used.





Safety Data Sheet

BOSS® MultiSeal 125

Section 1. Identification

Product Identifier

BOSS® MultiSeal 125

Synonyms

03970HTGR10; 03970WH10; 03970GY10; 03970BK10; 03970BR10; 03970ALGY10; 03970TN10; 03970OWH10; 03970LS10; 03970MB10;

03970RWTN10; 03970SPBZ10; 03970ST10

Manufacturer Stock

Numbers

N/A

Recommended use Uses advised against

Refer to Technical Data Refer to Technical Data

Manufacturer Contact

Address

Soudal Accumetric 350 Ring Road

(270) 769-3385

Elizabethtown, KY, 42701

USA

Phone

Emergency Phone

(800) 424-9300

(270) 765-2412

Fax

CHEMTREC

Section 2. Hazards Identification

Classification EYE DAMAGE/IRRITATION - Category 2A

HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD - Category

3

HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD -

Category 3

SENSITIZATION - SKIN - Category 1

Signal Word Pictogram

Warning



Hazard Statements Causes serious eye irritation

Harmful to aquatic life with long lasting effects

Harmful to aquatic life

May cause an allergic skin reaction

Precautionary Statements

Response If eye irritation persists: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If on skin: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Read label before use.

Wash contaminated clothing before reuse.

Prevention Avoid breathing dust/fume/gas/mist/ vapors/spray.

Avoid release to the environment

Contaminated work clothing must not be allowed out of the workplace.

Wash hands thoroughly after handling. Wear eye protection/face protection.

Wear protective gloves.

Storage N/A

Disposal Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

Additional Information None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
77-58-7	Dibutyltin dilaurate	0.1% - 1%
1760-24-3	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	1% - 5%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Comments Treat according to person's condition and specifics of exposure. DO NOT INDUCE VOMITING. Seek immediate medical attention. Ingestion

Inhalation Remove to fresh air. If symptoms persist, obtain appropriate medical attention. Skin Contact

Remove from skin and immediately flush with water for 15 minutes. Get medical attention if irritation or ill effects develop or persist.

Eye Contact

Immediately flush eyes with water for at least 15 minutes. Get medical

attention if irritation develops.

Section 5. Fire Fighting Measures

Suitable Extinguishing

Media

N/A

Unsuitable Extinguishing

N/A

Media

Flammability Limits in Air

Not determined

Auto-ignition Temperature Not determined

Extinguishing Media On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire

exposed containers.

Special Fire Fighting

Procedures

Fire responders must wear self-contained breathing apparatus and full protective equipment. Move fire-exposed containers if it can be done without risk to firefighters. If possible, control water run-off to prevent environmental

contamination.

Unusual Fire and Explosion Hazards

When involved in a fire, this material may decompose and produce the following toxic gases: carbon monoxide, carbon dioxide, nitrogen oxides, aldehydes, silicon dioxide, and various polymer compounds. Contact with water will release small quantities of flammable methanol.

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Observe all personal protective equipment recommendations as described in Section 8. Scrape all spilled materials for disposal. This material is not classified as a hazardous waste per 40 CFR 261.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable.

Section 7. Handling and Storage

Handling Avoid breathing vapors in top of shipping container. Keep container closed.

Use with adequate ventilation. Avoid contact with skin and clothing. Wash

throughly after handling.

Storage Keep container closed and store in a cool, well ventilated area, away from

water or moisture.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Ingredient Name **ACGIH OSHA** STEL Limits TLV **PEL** Dibutyltin dilaurate N/A N/A N/A N-beta-(aminoethyl)-gamma-N/A N/A N/A aminopropyltrimethoxysilane

Personal Protective N/A

Equipment

Respiratory Protection

Eye Protection Use proper protection - safety glasses as a minimum.

Skin Protection Wash at mealtimes and end of shift. If skin contact occurs, change

contaminated clothing as soon as possible and throughly flush affected areas with cool water. Chemical protective gloves are recommended.

Ventilation Local exhaust ventilation is recommended to maintain vapor level below TLV.

Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy

of existing engineering controls.

Note These precautions are for room temperature handling. Use at elevated

temperatures or aerosol/spray applications may require added precautions.

Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Various
Odor	Slight
Odor Threshold	N/A
Solubility	Water
	dilutable in
	wet stage
Partition coefficient Water/n-octanol	N/A
VOC%	10 g/L
Viscosity	N/A
Specific Gravity	1.42
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	200C
FP Method	N/A
Ph	N/A
Melting Point	Not
	determined
Boiling Point	Not
	determined
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not
	determined
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not
	determined
Vapor Density	Not
	determined

Section 10. Stability and Reactivity

Chemical Stability Stable

Hazardous polymerization Will not occur

Products

Hazardous Decomposition Thermal breakdown of this product during fire or very high heat conditions may

evolve the following hazardous decomposition products:

Carbon monoxide Carbon dioxide Nitrogen oxides Aldehydes Silicon Dioxide

Various polymer compounds

Materials to Avoid Oxidizing acids, amines, strong caustics, water

Conditions to Avoid Contact with incompatible materials and exposure to extreme temperatures.

Section 11. Toxicological Information

Carcinogenicity This product is not known to be a carcinogen. Teratogenicity This product is not known to be teratogenic. Mutagenicity This product is not known to be a mutagen.

Reproductive Toxin This product is not known to be a reproductive toxin.

Section 12. Ecological Information

Fate and Effects in Waste

Water Treatment Plants

Environmental Effects

Environmental Fate and

Distribution

Complete information is not yet available.

Complete information is not yet available.

Complete information is not yet available.

Section 13. Disposal

Waste Disposal Method

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number UN Proper Shipping Name N/A DOT Classification N/A
Packing Group N/A

DOT Road Shipment Information

DOT(USA): Caulking & Glaziers, NOI DOT Hazard Classification: None UN/NA Number: Not applicable

Label Required: None Marine Pollutant: None

Section 15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication

Standard 29 CFR 1910.1200.

TSCA Status All chemical substances found in this product comply with the Toxic

Substances Control Act inventory reporting requirements.

SARA Title III Section 302 None

Extremely Hazardous

Substances

SARA Titre III Section 304

CERCLA Substances

dangereuses

SARA Title III Section 313

Toxic Chemicals

California Proposition 65

None present or none present in regulated quantities.

This product contains the following chemical(s) listed by the State of California

under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:

None known

None

Canada Domestic Substances List All ingredients are listed on the DSL.

Section 16. Other Information

Revision Date 9/8/2015

Disclaimer The data contained herein is based upon information that Soudal Accumetric

believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.

Safety Data Sheet

BOSS® MultiSeal 125 Translucent

Section 1. Identification

Product Identifier BOSS® MultiSeal 125 Translucent

Synonyms 03970TR10 Manufacturer Stock 03970TR10

Numbers

Recommended use Refer to Technical Data
Uses advised against Refer to Technical Data

Manufacturer Contact

Address Soudal Accumetric

350 Ring Road

Elizabethtown, KY, 42701

USA

Phone Emergency Phone Fax

(270) 769-3385 (800) 424-9300 (270) 765-2412

CHEMTREC

Section 2. Hazards Identification

Classification EYE DAMAGE/IRRITATION - Category 2A

HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD -

Category 3

SENSITIZATION - SKIN - Category 1

SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2

Signal Word Warning

Pictogram

ctogram



Hazard Statements Causes serious eye irritation

Harmful to aquatic life with long lasting effects

May cause an allergic skin reaction

May cause damage to organsthrough prolonged or repeated exposure.

Precautionary Statements

Response Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If on skin: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Read label before use.

Wash contaminated clothing before reuse.

Prevention Avoid breathing dust/fume/gas/mist/ vapors/spray.

Avoid release to the environment

Contaminated work clothing must not be allowed out of the workplace.

Do not breathe dust/fume/gas/mist/ vapors/spray.

Wash hands thoroughly after handling. Wear eye protection/face protection.

Wear protective gloves.

Storage N/A

Disposal Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

Additional Information False

Section 3. Ingredients

CAS	Ingredient Name	Weight %
2224-33-1	Vinyl Oximino Silane	1% - 3%
1317-65-3	Calcium carbonate	10% - 30%
63148-62-9	Dimethylpolysiloxane	10% - 30%
22984-54-9	Methyl Oximino Silane	2% - 5%
112945-52-5	Amorphous fumed silica	4% - 8%
70131-67-8	Polydimethylsiloxanediol	45% - 80%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Comments Treat according to person's condition and specifics of exposure.

Ingestion DO NOT INDUCE VOMITING. Seek immediate medical attention.

Inhalation Remove to fresh air. If symptoms persist, obtain appropriate medical attention.

Skin Contact Remove from skin and immediately flush with water for 15 minutes. Get

medical attention if irritation or ill effects develop or persist.

Immediately flush eyes with water for at least 15 minutes. Get medical Eye Contact

attention if irritation develops.

Section 5. Fire Fighting Measures

N/A

N/A

Suitable Extinguishing

Media

Unsuitable Extinguishing

Media

Auto-ignition Temperature Not determined Lower Explosive Limit (%) Not applicable Upper Explosive Limit (%) Not applicable

Extinguishing Media

Carbon Dioxide, Dry Chemical, Foam, Water, Water Fog or Spray

Special Fire Fighting **Procedures**

Self-contained breathing apparatus and protective clothing should be worn

when fighting fires involving chemicals.

Unusual Fire or Explosion None known

Hazards

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Section 7. Handling and Storage

Other Precautions Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or

humid air. Provide ventilation during use to control MEKO within the exposure

guidelines or use respiratory protection.

Storage Keep container closed and store in a cool, well ventilated area, away from

water or moisture.

Handling Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container

closed. Do not take internally. Use reasonable care.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Vinyl Oximino Silane	N/A	N/A	N/A
	Calcium carbonate	10 mg/m3	5 mg/m3	N/A
	Dimethylpolysiloxane	N/A	N/A	N/A
	Methyl Oximino Silane	N/A	N/A	N/A
	Amorphous fumed silica	10 mg/m3	6 mg/m3	N/A
	Polydimethylsiloxanediol	N/A	N/A	N/A
Personal Protective Equipment	N/A			
Comment	Product evolves methyl ethyl keto humid air. Provide ventilation duri within the exposure guidelines or	ing use to control r	methyl ethyl keto	
Precautionary Measures	Avoid eye contact. Avoid skin contact. Avoid breathing vapor.			
Note	These precautions are for room t temperatures or aerosol/spray ap	•	•	
Respiratory Protection	Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.			
Skin Protection	Wash at mealtimes and end of sh contaminated clothing as soon a areas with cool water. Chemical	s possible and thr	oughly flush affe	
Eye Protection	Use proper protection - safety gl	asses as a minim	um.	

Section 9. Physical and Chemical Properties

Physical State	Paste	
Color	Translucent	
Odor	Slight	
Odor Threshold	N/A	
Solubility	Insoluble	
Partition coefficient Water/n-octanol	N/A	
VOC%	47.6 g/L (3.6%)	
Viscosity	1,200,000 cPs	
Specific Gravity	1.2	
Density lbs/Gal	10.01449	
Pounds per Cubic Foot	74.91355	
Flash Point	> 52C	
FP Method	Seta Closed	
	Cup	
Ph	Not	
	applicable	
Melting Point	Not	
	determined	

Boiling Point	Not	
	determined	
Boiling Range	N/A	
LEL	N/A	
UEL	N/A	
Evaporation Rate	Not	
	determined	
Flammability	N/A	
Decomposition Temperature	N/A	
Auto-ignition Temperature	N/A	
Vapor Pressure	Not	
	determined	
Vapor Density	Not	
	determined	

Section 10. Stability and Reactivity

Chemical Stability Stable

Hazardous polymerization Will not occur

Materials to Avoid /

Incompatibility

Conditions to Avoid None known

Section 11. Toxicological Information

Special Hazard Information Methyl Oximino Silane (22984-54-9) Possible skin sensitizer on Component Vinyl Oximino Silane (2224-33-1) Possible skin sensitizer

Oxidizing material can cause a reaction.

Component Toxicology

Information

Methyl Ethyl Ketoxime (MEKO) is formed upon contact with water or humid air. Male rodents exposed to MEKO vapor throughout their lifetime developed liver tumors. Since many commonly used chemicals cause liver tumors in rats and mice, additional testing is planned by the MEKO supplier to determine any relevance to humans. Until more data is known, exposure levels should be maintained as low as achievable.

Section 12. Ecological Information

Fate and Effects in Waste Complete information is not yet available.

Water Treatment Plants

Environmental Effects Environmental Fate and

Complete information is not yet available. Complete information is not yet available.

Distribution

Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number N/A
UN Proper Shipping Name N/A
DOT Classification N/A
Packing Group N/A

Ocean Shipment (IMDG) Not subject to IMDG code.

Air Shipment (IATA) Not subject to IATA regulations.

Road Shipment Not subject to DOT regulations.

Information (DOT)

Section 15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication

Standard 29 CFR 1910.1200.

TSCA Status All chemical substances found in this product comply with the Toxic

Substances Control Act inventory reporting requirements.

SARA Title III Section 302

Extremely Hazardous

Substances

SARA Titre III Section 304 None

CERCLA Substances

dangereuses

SARA Title III Section No components subject to 40 CFR 370

None

311/312

SARA Title III Section 313

Toxic Chemicals

None present or none present in regulated quantities.

California Proposition 65

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:

None known

Pennsylvania Limestone (1317-65-3)

Section 16. Other Information

Revision Date 9/8/2015

Disclaimer The data contained herein is based upon information that Soudal Accumetric

believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to

ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.