

Safety Data Sheet

BOSS™ 315 RTV Silicone Sealant

Section 1. Identification

Product Identifier BOSS™ 315 RTV Silicone Sealant
Synonyms C04010WH
Manufacture Stock Numbers N/A

Recommended use Refer to Technical Data
Uses advised against Refer to Technical Data

Manufacturer Contact

Address SOUDAL Accumetric
350 Ring Road
Elizabethtown, KY, 42701
USA

Phone

(270) 769-3385

Emergency Phone

(800) 424-
9300 Chemtrec

Fax

N/A

Section 2. Hazards Identification

Classification N/A

Signal Word

Pictogram

Hazard Statements N/A

Precautionary
Statements

Response N/A

Prevention Use only outdoors or in a well-ventilated area.

Storage N/A

Disposal N/A

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified Not a hazardous substance or mixture.

Section 3. Ingredients

CAS	Ingredient Name	Weight %
7631-86-9	Amorphous silica	5% - 10%
64742-46-7	Distillates (petroleum), hydrotreated middle	5% - 10%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid Measures

Eye Contact	Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes while holding the eyelids open. Obtain medical attention.
Skin Contact	No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
Inhalation	If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.
Ingestion	If irritation or discomfort occur, obtain medical advice.
Comments	Treat according to person's condition and specifics of exposure.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	N/A
Unsuitable Extinguishing Media	N/A
Auto-ignition Temperature	Not determined
Flammability Limits in Air	Not determined
Extinguishing Media	On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.
Special Fire Fighting Procedures	Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Unusual Fire or Explosion Hazards	None known

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release	Observe all personal protection equipment recommendations in Sections 5 and 8. Wipe or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.
Note	See Section 8 for information about personal protective equipment for spills. Contact Accumetric, LLC if additional information is required.

Section 7. Handling and Storage

Handling	Use adequate ventilation. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact.
Storage	Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Amorphous silica	10 mg/m ³	6 mg/m ³	Not Est.
Distillates (petroleum), hydrotreated middle	5 mg/m ³	5 mg/m ³	10 mg/m ³

Personal Protective Equipment

Goggles, Gloves

Component Exposure Limits

Component Name: Ethyltriacetoxysilane CAS Number: 17689-77-9
 Exposure Limits: See acetic acid comments
 Component Name: Methyltriacetoxysilane CAS Number: 4253-34-3
 Exposure Limits: See acetic acid comments
 Acetic acid is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm and ACGIH TLV: TWA 10 ppm, STEL 15 ppm.

Engineering Controls

Local Ventilation: None should be needed
 General Ventilation: Recommended

Eye Protection

Use proper protection - safety glasses as a minimum.

Skin Protection

Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended. Suitable Gloves: Handle in accordance with good industrial hygiene and safety practices.

Respiratory Protection

No respiratory protection should be needed. Suitable Respirator: None should be needed.

Precautionary Measures Comment

Avoid eye contact. Avoid skin contact. Use reasonable care. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection. When heated to temperatures above 150C (300F) in the presence of air, product can form formaldehyde vapors. Physical and health hazard information is readily available on the Material Safety Data Sheet. When heated to temperatures above 150C in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard, a known skin and respiratory sensitizer, and an irritant to the eyes, nose throat, skin and digestive system. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA Permissible Exposure Limit for formaldehyde.

Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require

added precautions.

Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Various
Odor	Acetic Acid
Odor Threshold	No data available
Solubility	No data available
Partition coefficient Water/n-octanol	No data available
Viscosity	Not applicable
Specific Gravity	1.007
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	>212F >100C
FP Method	Closed Cup
Ph	Not applicable
Melting Point	No data available
Boiling Point	Not applicable
Boiling Range	Not applicable
LEL	N/A
UEL	N/A
Evaporation Rate	Not applicable
Flammability	Not classified as a flammability hazard
Decomposition Temperature	No data available
Auto-ignition Temperature	No data available
Vapor Pressure	Not applicable
Vapor Density	No data available

NoteThe above information is not intended for use in preparing product specifications. Contact Soudal Accumentric before writing specifications.

Section 10. Stability and Reactivity

Chemical Stability	Stable
Hazardous Polymerization	Will not occur
Conditions to Avoid	None known
Materials to Avoid / Incompatibility	Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous vapors to form as described in Section 8.
Hazardous Decomposition Products	Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds Formaldehyde Silicon dioxide

Section 11. Toxicological Information

Special Hazard Information on Components	No known applicable information.
--	----------------------------------

Section 12. Ecological Information

Environmental Effects	Complete information is not yet available.
Environmental Fate and Distribution	Complete information is not yet available.
Fate and Effects in Waste Water Treatment Plants	Complete information is not yet available.

Section 13. Disposal

RCRA Hazard Class (40 CFR 261)	When a decision is made to discard this material, as received, is it classified as a hazardous waste? NO State or local laws may impose additional regulatory requirements regarding disposal.
Waste Disposal Method	We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes. This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	N/A
DOT Classification	N/A
Packing Group	N/A

Road Shipment
Information (DOT)

Ocean Shipment (IMDG)

Air Shipment (IATA)

Not subject to DOT
regulations.

Not subject to IMDG
code.

Not subject to IATA
regulations.

Section 15. Regulatory Information

	The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.
TSCA Status	All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.
SARA Title III Section 302 Extremely Hazardous Substances	None
SARA Title III Section 304 CERCLA Substances dangereuses	None
SARA Title III Section 311/312 Hazard Class	Acute: No Chronic: No Fire: No Pressure: No Reactive: No
SARA Title III Section 313 Toxic Chemicals	None present or none present in regulated quantities.
Note	Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.
California Proposition 65	This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known
New Jersey	Dimethyl siloxane, hydroxy-terminated (70131-67-8) Ethyltriacetoxysilane (17689-77-9) Methyltriacetoxysilane (4253-34-3) Silica, amorphous (7631-86-9) Hydrotreated middle petroleum distillates (64742-46-7)
Pennsylvania	Dimethyl siloxane, hydroxy-terminated (70131-67-8) Silica, amorphous (7631-86-9) Hydrotreated middle petroleum distillates (64742-46-7)

Section 16. Other Information

Revision Date

4/30/2015

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.