

Safety Data Sheet

BOSS™ 360 35 Year Sealant Siliconized Latex Caulk

Section 1. Identification

Product Identifier BOSS™ 360 35 Year Sealant Siliconized Latex Caulk
Synonyms 02735WH10; C39012BJB
Manufacture Stock Numbers N/A

Recommended use Refer to Technical Data
Uses advised against Refer to Technical Data

Manufacturer Contact

Address SOUDAL Accumetric
350 Ring Road
Elizabethtown, KY, 42701
USA

Phone

(270) 769-3385

Emergency Phone

(800) 424-
9300 Chemtrec

Fax

N/A

Section 2. Hazards Identification

Classification N/A
Signal Word
Pictogram
Hazard Statements N/A
Precautionary
Statements
Response N/A
Prevention N/A
Storage N/A
Disposal N/A

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Section 3. Ingredients

CAS	Ingredient Name	Weight %
7632-00-0	Sodium nitrate	0.1% - Max
27138-31-4	Dipropylene glycol dibenzoate	1% - 5%
13463-67-7	Titanium Dioxide	1% - 5%
64742-46-7	Distillates (petroleum), hydrotreated middle	1% - 5%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid Measures

Skin Contact	Wash affected area with soap and water.
Eye Contact	Immediately flush with large amounts of water. If irritation occurs, seek medical attention.
Ingestion	No first aid should be needed.
Inhalation	Remove to fresh air. If symptoms persist, obtain appropriate medical attention.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	N/A
Unsuitable Extinguishing Media	N/A
Extinguishing Media	Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog
Special Fire Fighting Procedures	Non-flammable (aqueous emulsion). After water evaporates, remaining material will burn. Breathing apparatus required when fighting fires in enclosed areas.
Unusual Fire or Explosion Hazards	Product will not burn, but may splatter if temperature exceeds boiling point of water. Dried solids can burn, giving off oxides of carbon.

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Section 7. Handling and Storage

Handling Avoid breathing vapors in top of shipping container. Keep container closed. Use with adequate ventilation. Avoid contact with skin and clothing. Wash thoroughly after handling.

Storage Store in a cool dry place. Protect from freezing and excessive heat.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Sodium nitrate	N/A	N/A	N/A
Dipropylene glycol dibenzoate	N/A	N/A	N/A
Titanium Dioxide	10 mg/m ³	15 mg/m ³	N/A
Distillates (petroleum), hydrotreated middle	5 mg/m ³	5 mg/m ³	10 mg/m ³

Personal Protective Equipment N/A

Eye Protection Safety goggles or glasses with side shields are recommended.

Respiratory Protection No respiratory protection should be needed with good local ventilation.

Ventilation Local exhaust ventilation is recommended to maintain vapor level below TLV.

Skin Protection Impervious gloves are suggested.

Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Various
Odor	Slight
Odor Threshold	N/A
Solubility	Dilutable in wet stage
Partition coefficient Water/n-octanol	N/A
Viscosity	750,000 cPs
Specific Gravity	1.66
Density lbs/Gal	13.8
Pounds per Cubic Foot	103.63042
Flash Point	Not determined
FP Method	N/A
Ph	7.85
Melting Point	0C
Boiling Point	100C
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Slower than n-Butyl acetate
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not determined
Vapor Density	Lighter than air

NoteThe above information is not intended for use in preparing product specifications. Contact SOUDAL Accumentric before writing specifications.

Section 10. Stability and Reactivity

Chemical Stability	Stable
Hazardous Polymerization	Will not occur
Conditions to Avoid	None known
Materials to Avoid / Incompatibility	None known

Section 11. Toxicological Information

Component Toxicology Information	No known applicable information.
Special Hazard Information on Components	No known applicable information.

Section 12. Ecological Information

Environmental Effects Complete information is not yet available.
Environmental Fate and Distribution Complete information is not yet available.
Fate and Effects in Waste Water Treatment Plants Complete information is not yet available.

Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes. This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	N/A
DOT Classification	N/A
Packing Group	N/A

Ocean Shipment (IMDG) Not subject to IMDG code.
Road Shipment Information (DOT) Not subject to DOT regulations.
Air Shipment (IATA) Not subject to IATA regulations.

Section 15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

SARA Title III Section 302 Extremely Hazardous Substances None

SARA Title III Section 304 CERCLA Substances dangereuses None

SARA Title III Section 313 Toxic Chemicals None present or none present in regulated quantities.

California Proposition 65 This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known

Section 16. Other Information

Revision Date

5/19/2015

Disclaimer

The data contained herein is based upon information that SOUDAL Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.