

Safety Data Sheet

BOSS™ 380 Contractor's Silicone Sealant

Section 1. Identification

| | | | |
|------------------------------|---|-------------------------|-----|
| Product Identifier | BOSS™ 380 Contractor's Silicone Sealant | | |
| Synonyms | 02142CL10; 02142WH10; 02142BK10; 02142AL10; 02142BZ10; 02142AM10; 02142BW10; 03336CL01; 02142CW10; 02142GR10; 02142MH10; 02142TN10; 02142TW10 | | |
| Manufacture Stock Numbers | N/A | | |
| Recommended use | Refer to Technical Data | | |
| Uses advised against | Refer to Technical Data | | |
| Manufacturer Contact Address | SODAL Accumetric 350 Ring Road Elizabethtown, KY, 42701 USA | | |
| | Phone | Emergency Phone | Fax |
| | (270) 769-3385 | (800) 424-9300 Chemtrec | N/A |

Section 2. Hazards Identification

| | |
|----------------------------------|---|
| Classification | N/A |
| Signal Word | |
| Pictogram | |
| Hazard Statements | N/A |
| Precautionary Statements | |
| Response | N/A |
| Prevention | Use only outdoors or in a well-ventilated area. |
| Storage | N/A |
| Disposal | N/A |
| Ingredients of unknown toxicity | 0% |
| Hazards not Otherwise Classified | Not a hazardous substance or mixture. |

Section 3. Ingredients

| CAS | Ingredient Name | Weight % |
|------------|--|-----------|
| 64742-46-7 | Distillates (petroleum), hydrotreated middle | 20% - 30% |
| 7631-86-9 | Amorphous silica | 5% - 10% |

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid Measures

| | |
|--------------|---|
| Eye Contact | Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes while holding the eyelids(s) open. If contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Take care not to rinse contaminated water into the unaffected eye or unto the face. Immediately obtain medical attention. |
| Skin Contact | Remove contaminated clothing, shoes, and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Flush with lukewarm gently flowing water for 15 minutes. If irritation persists, repeat flushing. If irritation persists, obtain medical advice. |
| Inhalation | If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice. |
| Ingestion | If irritation or discomfort occur, obtain medical advice. |
| Comments | Treat according to person's condition and specifics of exposure. |

Section 5. Fire Fighting Measures

| | |
|-----------------------------------|--|
| Suitable Extinguishing Media | N/A |
| Unsuitable Extinguishing Media | N/A |
| Auto-ignition Temperature | Not determined |
| Flammability Limits in Air | Not determined |
| Extinguishing Media | On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers. |
| Special Fire Fighting Procedures | Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. |
| Unusual Fire or Explosion Hazards | None known |
| Hazardous Decomposition Products | Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds Formaldehyde Silicon dioxide Depending on color, may also evolve: Metal oxides |

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release Observe all personal protection equipment recommendations. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Section 7. Handling and Storage

Handling Use with adequate ventilation. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to acetic acid within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container closed.

Storage Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits

| Ingredient Name | ACGIH TLV | OSHA PEL | STEL |
|--|-----------|----------|----------|
| Distillates (petroleum), hydrotreated middle | 10 mg/m3 | 6 mg/m3 | Not Est. |
| Amorphous silica | 5 mg/m3 | 5 mg/m3 | 10 mg/m3 |

Personal Protective Equipment

Goggles, Gloves

Exposure Controls

Acetic acid is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm and ACGIH TLV: TWA 10 ppm, STEL 15 ppm.

Engineering Controls

Local Ventilation: Recommended
General Ventilation: Recommended

Eye Protection

Safety goggles or glasses with side shields are recommended.

Skin Protection

Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended. Suitable Gloves: Avoid skin contact by implementing good industrial hygiene practices and procedures. Select and use gloves and/or protective clothing to further minimize the potential for skin contact. Consult with your glove and/or personnel protective equipment manufacturer for selection of appropriate compatible materials.

Respiratory Protection

Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls. Suitable Respirator: Respiratory protection is not needed under ambient conditions. If vapor are generated when material is heated or handled, the following is advised. General or local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MHSA approved respirator.

Comment

Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection. When heated to temperatures above 150C (300F) in the presence of air, product can form formaldehyde vapors. Physical and health hazard information is readily available on the Material Safety Data Sheet.

Precautionary Measures

Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container closed. Use reasonable care.

Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions.

Section 9. Physical and Chemical Properties

| | |
|---------------------------------------|------------------|
| Physical State | Paste |
| Color | Various |
| Odor | Acetic Acid Odor |
| Odor Threshold | N/A |
| Solubility | Not Determined |
| Partition coefficient Water/n-octanol | N/A |
| Viscosity | Not Determined |
| Specific Gravity | 0.96 |
| Density lbs/Gal | N/A |
| Pounds per Cubic Foot | N/A |
| Flash Point | Not Applicable |
| FP Method | N/A |
| Ph | Not Determined |
| Melting Point | Not Determined |
| Boiling Point | Not Determined |
| Boiling Range | N/A |
| LEL | N/A |
| UEL | N/A |
| Evaporation Rate | Not Determined |
| Flammability | N/A |
| Decomposition Temperature | N/A |
| Auto-ignition Temperature | N/A |
| Vapor Pressure | Not Determined |
| Vapor Density | Not Determined |

Note The above information is not intended for use in preparing product specifications. Contact SOUDAL Accumentric before writing specifications.

Section 10. Stability and Reactivity

| | |
|--------------------------------------|---|
| Conditions to Avoid | None known |
| Hazardous Polymerization | Will not occur |
| Chemical Stability | Stable |
| Materials to Avoid / Incompatibility | Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous vapors to form as described in Section 8. |

Section 11. Toxicological Information

Special Hazard Information on Components No known applicable information.

Section 12. Ecological Information

Environmental Effects Complete information is not yet available.
Environmental Fate and Distribution Complete information is not yet available.
Fate and Effects in Waste Water Treatment Plants Complete information is not yet available.

Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes. This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

| | |
|-------------------------|-----|
| UN Number | N/A |
| UN Proper Shipping Name | N/A |
| DOT Classification | N/A |
| Packing Group | N/A |
| | |

| | |
|---------------------------------|----------------------------------|
| Ocean Shipment (IMDG) | Not subject to IMDG code. |
| Road Shipment Information (DOT) | Not subject to DOT regulations. |
| Air Shipment (IATA) | Not subject to IATA regulations. |

Section 15. Regulatory Information

| | |
|---|--|
| | The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200. |
| TSCA Status | All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements. |
| SARA Title III Section 302 Extremely Hazardous Substances | None |
| SARA Title III Section 304 CERCLA Substances dangereuses | None |
| SARA Title III Section 312 Hazard Class | Acute: Yes Chronic: No Fire: No Pressure: No Reactive: No |
| SARA Title III Section 313 Toxic Chemicals | None present or none present in regulated quantities. |
| Note | Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold. |
| California Proposition 65 | This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known |
| Massachusetts | Silica, amorphous (7631-86-9) Depending on color, may also contain: Titanium dioxide (13463-67-7) |
| New Jersey | Dimethyl siloxane, hydroxy-terminated (70131-67-8) Ethyltriacetoxysilane (17689-77-9) Hydrotreated medium petroleum distillates (64742-46-7) Methyltriacetoxysilane (4253-34-3) Silica, amorphous (7631-86-9) Depending on color, may also contain: Carbon black (1333-86-4) Titanium dioxide (13463-67-7) |
| Pennsylvania | Dimethyl siloxane, hydroxy-terminated (70131-67-8) Hydrotreated medium petroleum distillates (64742-46-7) Silica, amorphous (7631-86-9) Depending on color, may also contain: Titanium dioxide (13463-67-7) |

Section 16. Other Information

| | |
|---------------|--|
| Revision Date | 2/10/2015 |
| Disclaimer | The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. |