

# Safety Data Sheet

## BOSS® 389 Marine Silicone Sealant

### Section 1. Identification

Product Identifier	BOSS® 389 Marine Silicone Sealant		
Synonyms	04230CL10; 04230WH10		
Manufacturer Stock Numbers	04230CL10; 04230WH10		
Recommended use	Refer to Technical Data		
Uses advised against	Refer to Technical Data		
Manufacturer Contact			
Address	SODAL Accumetric 350 Ring Road Elizabethtown, KY, 42701 USA		
	Phone	Emergency Phone	Fax
	(270) 769-3385	(800) 424-9300 CHEMTREC	N/A

### Section 2. Hazards Identification

Classification	N/A
Signal Word	
Pictogram	
Hazard Statements	N/A
Precautionary Statements	
Response	N/A
Prevention	Use only outdoors or in a well-ventilated area.
Storage	N/A
Disposal	N/A
Ingredients of unknown toxicity	0%
Hazards not Otherwise Classified	

### Section 3. Ingredients

CAS	Ingredient Name	Weight %
7631-86-9	Amorphous silica	5% - 10%
64742-46-7	Distillates (petroleum), hydrotreated middle	5% - 10%

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-Aid Measures

Eye Contact	Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes while holding the eyelids open. Obtain medical attention.
Skin Contact	Remove contaminated clothing, shoes, and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Flush with lukewarm gently flowing water for 15 minutes. If irritation persists, repeat flushing. If irritation persists, obtain medical advice.
Inhalation	Material is not likely to present an inhalation hazard at ambient conditions. If material is heated or vapor are generated, care should be taken to prevent inhalation. In case of exposure to vapor, move to fresh air.
Ingestion	If irritation or discomfort occur, obtain medical advice.
Comments	Treat according to person's condition and specifics of exposure.

### Section 5. Fire Fighting Measures

Suitable Extinguishing Media	N/A
Unsuitable Extinguishing Media	N/A
Auto-ignition Temperature	Not determined
Flammability Limits in Air	Not determined
Extinguishing Media	On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.
Special Fire Fighting Procedures	Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Unusual Fire or Explosion Hazards	None known

### Section 6. Accidental Release Measures

Steps to be taken in case of spill or release	Observe all personal protection equipment recommendations. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate
---	--

since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

## Section 7. Handling and Storage

### Handling

Use adequate ventilation. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact. Avoid breathing vapors, mist, dust or fumes. Keep container closed. Do not take internally.

### Storage

Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

## Section 8. Exposure Controls/Personal Protection

### Occupational Exposure Limits

Ingredient Name	ACGIH TLV OSHA PEL STEL		
Amorphous silica	10 mg/m3	6 mg/m3	Not Est.
Distillates (petroleum), hydrotreated middle	5 mg/m3	5 mg/m3	10 mg/m3

### Personal Protective Equipment

Goggles, Gloves

### Engineering Controls

Local Ventilation: Recommended  
General Ventilation: Recommended

### Component Exposure Limits

Component Name: Hydrotreated middle petroleum distillates  
CAS Number: 64742-46-7  
Exposure Limits: OSHA PEL (final rule) and ACGIH TLV for oil mists: TWA 5 mg/m3

Component Name: Ethyltriacetoxysilane  
CAS Number: 17689-77-9  
Exposure Limits: See acetic acid comments

Component Name: Methyltriacetoxysilane  
CAS Number: 4253-34-3  
Exposure Limits: See acetic acid comments

Component Name: C.I. Pigment Green 50  
CAS Number: 68186-85-6  
Exposure Limits: Observe limits: Nickel - OSHA PEL and ACGIH TLV: TWA 1

mg/m<sup>3</sup>. Cobalt - OSHA PEL (final rule) and ACGIH TLV: TWA 0.05 mg/m<sup>3</sup>.

Acetic acid is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm and ACGIH TLV: TWA 10 ppm, STEL 15 ppm.

Eye Protection

Use proper protection - safety glasses as a minimum.

Skin Protection

Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves:

Avoid skin contact by implementing good industrial hygiene practices and procedures. Select and use gloves and/or protective clothing to further minimize the potential for skin contact. Consult with your glove and/or personnel protective equipment manufacturer for selection of appropriate compatible materials.

Respiratory Protection

Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.

Suitable Respirator:

Respiratory protection is not needed under ambient conditions.

If vapor/mist/dust/fumes are generated when material is heated or handled, respiratory protection recommended. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MHSA approved respirator. Protection provided by air purifying respirators against exposure to any hazardous chemical limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure level are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Precautionary Measures

Avoid eye contact. Avoid skin contact. Avoid breathing vapor, mist, dust or fumes. Keep container closed. Do not take internally. Use reasonable care.

Comment

Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection.

When heated to temperatures above 150C (300F) in the presence of air, product can form formaldehyde vapors. Physical and health hazard information is readily available on the Material Safety Data Sheet.

Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions.

## Section 9. Physical and Chemical Properties

Physical State	Paste
Color	See product label
Odor	Acetic Acid
Odor Threshold	No data available

Solubility	No data available
Partition coefficient Water/n-octanol	No data available
VOC%	29 g/L
Viscosity	Not applicable
Specific Gravity	1.007
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	>100C
FP Method	Closed Cup
Ph	Not applicable
Melting Point	No data available
Boiling Point	Not applicable
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not applicable
Flammability	Not classified as a flammability hazard
Decomposition Temperature	No data available
Auto-ignition Temperature	No data available
Vapor Pressure	Not applicable
Vapor Density	No data available

#### Note

The above information is not intended for use in preparing product specifications. Contact Soudal Accumentric before writing specifications.

## Section 10. Stability and Reactivity

Chemical Stability	Stable
Hazardous Polymerization	Will not occur
Conditions to Avoid	None known
Materials to Avoid / Incompatibility	Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous vapors to form as described in Section 8.

Hazardous Decomposition Products	Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Silicon dioxide. Nitrogen oxides. Metal oxides. Sulfur oxides.
----------------------------------	--

## Section 11. Toxicological Information

Component Toxicology Information	Inhalation of fumes may result in metal fume fever, a flu-like illness with symptoms of metallic taste, fever and chills, aches, chest tightness and cough.
Información Especial sobre Riesgo en los Componentes	Espinela verde de titanita y cobalto (68186-85-6) IARC Grupo 2B. Compuesto de cobalto.

## Section 12. Ecological Information

Fate and Effects in Waste Water Treatment Plants	Complete information is not yet available.
Environmental Effects	Complete information is not yet available.
Environmental Fate and Distribution	Complete information is not yet available.

## Section 13. Disposal

Waste Disposal Method	<p>We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.</p> <p>This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.</p>
-----------------------	--

## Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	N/A
DOT Classification	N/A
Packing Group	N/A
Air Shipment (IATA)	Not subject to IATA regulations.
Ocean Shipment (IMDG)	Not subject to IMDG code.
Road Shipment Information (DOT)	Not subject to DOT regulations.

## Section 15. Regulatory Information

	The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.
TSCA Status	All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.
SARA Title III Section 302 Extremely Hazardous Substances	None
SARA Title III Section 304 CERCLA Substances dangereuses	None
SARA Título III Sección 311/312 Clase de Peligro	Agudo: No Crónico: Yes Fuego: No Presión: No Reactivo: No
SARA Title III Section 313 Toxic Chemicals	C.I. Pigment Green 50 (68186-85-6)
Note	Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.
California Proposition 65	This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known
Massachusetts	Silica, amorphous (7631-86-9) Carbon black (1333-86-4) Titanium dioxide (13463-67-7) 10, 10-Oxydiphenoxarsine (58-36-6)
New Jersey	Dimethyl siloxane, hydroxy-terminated (70131-67-8) Hydrotreated middle petroleum distillates (64742-46-7) Silica, amorphous (7631-86-9) Polydimethylsiloxane (63148-62-9) Tetrabenzo-5,10,15,20-diazaporphyrinephthalocyanine (Pigment blue 15) (147-14-8) Iron oxide (1332-37-2) Carbon black (1333-86-4) Titanium dioxide (13463-67-7) C.I. Pigment Green 50 (68186-85-6)
Pennsylvania	Dimethyl siloxane, hydroxy-terminated (70131-67-8) Hydrotreated middle petroleum distillates (64742-46-7) Silica, amorphous (7631-86-9) Polydimethylsiloxane (63148-62-9) Tetrabenzo-5,10,15,20-diazaporphyrinephthalocyanine (Pigment blue 15) (147-14-8) Carbon black (1333-86-4) Titanium dioxide (13463-67-7)

## Section 16. Other Information

Revision Date 6/17/2015

Disclaimer The data contained herein is based upon information that Soudal

Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.