

Safety Data Sheet

BOSS® 393 Gutter Seal

Section 1. Identification

Product Identifier BOSS® 393 Gutter Seal Synonyms 39303; 39301; 39300

Manufacturer Stock

Numbers

03933CL10; 03933WH10; 03933AL10; C04203CL; C04203WH; C04203AL

Recommended use Refer to Technical Information
Uses advised against Refer to Technical Information

Manufacturer Contact

Address

Soudal Accumetric 350 Ring Road

Elizabethtown, KY, 42701

USA

Phone Emergency Phone Fax

(270) 769-3385 (800) 424-9300 (270) 765-2412

CHEMTREC

Section 2. Hazards Identification

Classification EYE DAMAGE/IRRITATION - Category 2A

HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD -

Category 3

SENSITIZATION - SKIN - Category 1

SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2

Signal Word Warning

Pictogram



Hazard Statements Causes serious eye irritation

Harmful to aquatic life with long lasting effects

May cause an allergic skin reaction

May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

Response Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If on skin: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Read label before use.

Wash contaminated clothing before reuse.

Prevention Avoid breathing dust/fume/gas/mist/ vapors/spray.

Avoid release to the environment

Contaminated work clothing must not be allowed out of the workplace.

Do not breathe dust/fume/gas/mist/ vapors/spray.

Wash hands thoroughly after handling. Wear eye protection/face protection.

Wear protective gloves.

Storage N/A

Disposal Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

Additional Information None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
22984-54-9	Methyl Oximino Silane	1% - 5%
1760-24-3	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	1% - 5%
2224-33-1	Vinyl Oximino Silane	1% - 5%
63148-62-9	Dimethylpolysiloxane	10% - 30%
112945-52-5	Amorphous fumed silica	5% - 10%
64741-44-2	Distillates (petroleum), straight-run middle	5% - 10%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Comments Treat according to person's condition and specifics of exposure.

Ingestion DO NOT INDUCE VOMITING. Seek immediate medical attention.

Skin Contact Remove from skin and immediately flush with water for 15 minutes. Get

medical attention if irritation or ill effects develop or persist.

Eye Contact Immediately flush eyes with water for at least 15 minutes. Get medical

attention if irritation develops.

Section 5. Fire Fighting Measures

Suitable Extinguishing

Media

Inhalation

On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire

Remove to fresh air. If symptoms persist, obtain appropriate medical attention.

exposed containers.

Unsuitable Extinguishing

Media

None known

Special Fire Fighting

Procedures

Self-contained breathing apparatus and protective clothing should be worn

when fighting fires involving chemicals.

Unusual Fire or Explosion None known

Hazards

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Section 7. Handling and Storage

Other Precautions

Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control MEKO within the exposure guidelines or use respiratory protection.

Storage Keep container closed and store in a cool, well ventilated area, away from

water or moisture.

Handling Avoid breathing vapors in top of shipping container. Keep container closed.

Use with adequate ventilation. Avoid contact with skin and clothing. Wash

throughly after handling.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Methyl Oximino Silane	N/A	N/A	N/A
N-beta-(aminoethyl)-gamma- aminopropyltrimethoxysilane	N/A	N/A	N/A
Vinyl Oximino Silane	N/A	N/A	N/A
Dimethylpolysiloxane	N/A	N/A	N/A
Amorphous fumed silica	10 mg/m3	6 mg/m3	N/A
Distillates (petroleum), straight-run middle	N/A	N/A	N/A

Personal Protective Equipment

Goggles, Gloves

Respiratory Protection

Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy

of existing engineering controls.

Eye Protection

Use proper protection - safety glasses as a minimum.

Skin Protection

Wash at mealtimes and end of shift. If skin contact occurs, change contaminated clothing as soon as possible and throughly flush affected areas with cool water. Chemical protective gloves are recommended.

Precautionary Measures

Avoid eye contact. Avoid skin contact. Avoid breathing vapor.

Comment

Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control methyl ethyl ketoxime

within the exposure guidelines or use respiratory protection.

Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions.

Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Clear
Odor	Slight
Odor Threshold	N/A
Solubility	Water
	dilutable in
	wet stage
Partition coefficient Water/n-octanol	N/A
VOC%	16 g/L (<3%)
Viscosity	N/A

Specific Gravity	1
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	Not
	applicable
FP Method	N/A
Ph	Not
	applicable
Melting Point	Not
	determined
Boiling Point	Not
	determined
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not
	determined
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not
	determined
Vapor Density	Not
	determined

Note The above information is not intended for use in preparing product

specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

Chemical Stability Stable

Hazardous polymerization Will not occur

Materials to Avoid /

Incompatibility

Oxidizing material can cause a reaction.

Conditions to Avoid None known

Section 11. Toxicological Information

Special Hazard Information Methyl Oximino Silane (22984-54-9) Possible skin sensitizer on Component Vinyl Oximino Silane (2224-33-1) Possible skin sensitizer

Carcinogenicity This product is not known to be a carcinogen.

Teratogenicity This product is not known to be teratogenic.

Mutagenicity This product is not known to be a mutagen.

Reproductive Toxin This product is not known to be a reproductive toxin.

Sensitizer Product releases MEKO, which is a potential skin sensitizer.

Component Toxicology Information

Methyl Ethyl Ketoxime (MEKO) is formed upon contact with water or humid air. Male rodents exposed to MEKO vapor throughout their lifetime developed liver tumors. Since many commonly used chemicals cause liver tumors in rats and mice, additional testing is planned by the MEKO supplier to determine any relevance to humans. Until more data is known, exposure levels should be maintained as low as achievable.

Section 12. Ecological Information

Fate and Effects in Waste

Complete information is not yet available.

Water Treatment Plants
Environmental Effects

Complete information is not yet available.

Environmental Fate and

Complete information is not yet available.

Distribution

Section 13. Disposal

Waste Disposal Method

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number N/A

UN Proper Shipping Name Not regulated DOT Classification Not regulated Packing Group Not regulated

Ocean Shipment (IMDG) Not subject to IMDG code.

Air Shipment (IATA) Not subject to IATA regulations.

Section 15. Regulatory Information

TSCA Status All chemical substances found in this product comply with the Toxic

Substances Control Act inventory reporting requirements.

SARA Title III Section 302 Extremely Hazardous

Substances

None

SARA Titre III Section 304

None

CERCLA Substances

dangereuses

SARA Title III Section 312

Hazard Class

Acute: Yes Chronic: Yes Fire: No Pressure: No Reactive: No

SARA Title III Section 313

Toxic Chemicals

None present or none present in regulated quantities.

California Proposition 65 This product contains the following chemical(s) listed by the State of California

> under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:

None known

Massachusetts Silica, amorphous fumed (112945-52-5)

New Jersey Silica, amorphous (112945-52-5)

Dimethyl siloxane, hydroxy-terminated (70131-67-8)

Methyl oximino silane (22984-54-9) Vinyl oximino silane (2224-33-1)

Distillates (petroleum), hydrotreated middle (64742-46-7)

Pennsylvania Silica, amorphous (112945-52-5)

Dimethyl siloxane, hydroxy-terminated (70131-67-8)

Methyl oximino silane (22984-54-9) Vinyl oximino silane (2224-33-1)

Distillates (petroleum), hydrotreated middle (64742-46-7)

Section 16. Other Information

Revision Date 11/9/2015

Disclaimer The data contained herein is based upon information that Soudal Accumetric

> believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.