

Safety Data Sheet

BOSS® 398 Neutral Non-Corrosive Premium Silicone

Section 1. Identification

Product Identifier Synonyms Manufacturer Stock Numbers	BOSS® 398 Neutral Non 39802; 39800 04200CL10; 04200BK10;	-Corrosive Premium Silico ; C04045CL; C04046BK	ne
Recommended use Uses advised against	Refer to Technical Inform Refer to Technical Inform		
Manufacturer Contact Address	Soudal Accumetric 350 Ring Road Elizabethtown, KY, 42701 USA		
	Phone (270) 769-3385	Emergency Phone (800) 424-9300 CHEMTREC	Fax (270) 765-2412

Section 2. Hazards Identification

Classification	EYE DAMAGE/IRRITATION - Category 2A HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD - Category 3 SENSITIZATION - SKIN - Category 1 SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2
Signal Word	Warning

Pictogram	
Hazard Statements	Causes serious eye irritation Harmful to aquatic life with long lasting effects May cause an allergic skin reaction May cause damage to organs through prolonged or repeated exposure.
Precautionary Statements	
Response	Get medical advice/attention if you feel unwell. If eye irritation persists: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If on skin: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Read label before use. Wash contaminated clothing before reuse.
Prevention	Avoid breathing dust/fume/gas/mist/ vapors/spray. Avoid release to the environment Contaminated work clothing must not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/ vapors/spray. Wash hands thoroughly after handling. Wear eye protection/face protection. Wear protective gloves.
Storage	N/A
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Ingredients of unknown toxicity	0%
Hazards not Otherwise Classified Additional Information	None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
1760-24-3	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	1% - 5%
2224-33-1	Vinyl Oximino Silane	1% - 5%
22984-54-9	Methyl Oximino Silane	1% - 5%
63148-62-9	Dimethylpolysiloxane	10% - 30%
112945-52-5	Amorphous fumed silica	5% - 10%
64741-44-2	Distillates (petroleum), straight-run middle	5% - 10%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Comments	Treat according to person's condition and specifics of exposure.
Ingestion	DO NOT INDUCE VOMITING. Seek immediate medical attention.
Inhalation	Remove to fresh air. If symptoms persist, obtain appropriate medical attention.
Skin Contact	Remove from skin and immediately flush with water for 15 minutes. Get medical attention if irritation or ill effects develop or persist.
Eye Contact	Immediately flush eyes with water for at least 15 minutes. Get medical attention if irritation develops.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Carbon dioxide, dry chemcial, foam, water, water fog or spray
Unsuitable Extinguishing Media	None known
Special Fire Fighting Procedures	Self-contained breathing apparatus and protective clothing should be worn when fighting fires involving chemicals.
Unusual Fire or Explosion Hazards	None known

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release	Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Section 7. Handling and Storage

Other Precautions	Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control MEKO within the exposure guidelines or use respiratory protection.
Storage	Keep container closed and store in a cool, well ventilated area, away from water or moisture.

Handling

Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container closed. Do not take internally. Use reasonable care.

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	N-beta-(aminoethyl)-gamma- aminopropyltrimethoxysilane	N/A	N/A	N/A
	Vinyl Oximino Silane	N/A	N/A	N/A
	Methyl Oximino Silane	N/A	N/A	N/A
	Dimethylpolysiloxane	N/A	N/A	N/A
	Amorphous fumed silica	10 mg/m3	6 mg/m3	N/A
	Distillates (petroleum), straight-run middle	N/A	N/A	N/A
Personal Protective Equipment	Goggles, Gloves			
Respiratory Protection	Use respiratory protection unless adequate exh exposure assessment demonstrates that exposi guidelines. Industrial Hygiene Personnel can as of existing engineering controls.	sures are with	in exposur	е
	exposure assessment demonstrates that exposiguidelines. Industrial Hygiene Personnel can as	sures are with ssist in judgin	in exposur	е
Eye Protection	exposure assessment demonstrates that exposignidelines. Industrial Hygiene Personnel can as of existing engineering controls.	sures are with ssist in judgin himum. act occurs, ch throughly flus	in exposure g the adequ hange sh affected	е
Eye Protection Skin Protection	 exposure assessment demonstrates that exposiguidelines. Industrial Hygiene Personnel can as of existing engineering controls. Use proper protection - safety glasses as a mir Wash at mealtimes and end of shift. If skin cont contaminated clothing as soon as possible and 	sures are with ssist in judgin himum. act occurs, ch throughly flus es are recomr	in exposure g the adequ hange sh affected	е
Respiratory Protection Eye Protection Skin Protection Precautionary Measures Comment	 exposure assessment demonstrates that exposing guidelines. Industrial Hygiene Personnel can as of existing engineering controls. Use proper protection - safety glasses as a mir Wash at mealtimes and end of shift. If skin cont contaminated clothing as soon as possible and areas with cool water. Chemical protective glow 	sures are with ssist in judgin himum. act occurs, ch throughly flus es are recomr thing vapor. when exposed rol methyl ethy	in exposure g the adequant ange sh affected mended.	e Jacy

Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Refer to
00101	product label
Odor	Slight
Odor Threshold	N/A
Solubility	Insoluble
Partition coefficient Water/n-octanol	N/A
VOC%	2.8% (w/w)
Viscosity	N/A
Specific Gravity	1.2
Density lbs/Gal	10.01449
Pounds per Cubic Foot	74.91355
Flash Point	> 52C

FP Method	Seta Closed
	Cup
Ph	Not
	applicable
Melting Point	Not
	determined
Boiling Point	Not
	determined
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not
	determined
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not
	determined
Vapor Density	Not
	determined

Note

The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

Chemical Stability	Stable
Hazardous polymerization	Will not occur
Materials to Avoid /	Oxidizing material can cause a reaction.
Incompatibility	
Conditions to Avoid	None known

Section 11. Toxicological Information

Special Hazard InformationMethyl Oximino Silane (22984-54-9) Possible skin sensitizeron ComponentVinyl Oximino Silane (2224-33-1) Possible skin sensitizerComponent ToxicologyMethyl Ethyl Ketoxime (MEKO) is formed upon contact with water or humid air.
Male rodents exposed to MEKO vapor throughout their lifetime developed liver
tumors. Since many commonly used chemicals cause liver tumors in rats and
mice, additional testing is planned by the MEKO supplier to determine any
relevance to humans. Until more data is known, exposure levels should be
maintained as low as achievable.

Section 12. Ecological Information

Fate and Effects in Waste Complete information is not yet available. Water Treatment Plants

Environmental Effects	Complete information is not yet available.
Environmental Fate and	Complete information is not yet available.
Distribution	

Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	Not regulated
DOT Classification	Not regulated
Packing Group	Not regulated
Ocean Shipment (IMDG)	Not subject to IMDG code.
Air Shipment (IATA)	Not subject to IATA regulations.

Section 15. Regulatory Information

	The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.
TSCA Status	All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.
SARA Title III Section 302 Extremely Hazardous Substances	None
SARA Titre III Section 304 CERCLA Substances dangereuses	None
SARA Title III Section 311/312	No components subject to 40 CFR 370
SARA Title III Section 313 Toxic Chemicals	None present or none present in regulated quantities.
California Proposition 65	This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known
Pennsylvania	Limestone (1317-65-3)

Section 16. Other Information

Revision Date

11/9/2015

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.