

Safety Data Sheet

BOSS® 840 Non-Corrosive Marine Sealant

Section 1. Identification

Product Identifier BOSS® 840 Non-Corrosive Marine Sealant

Synonyms 84001; 84000

Manufacturer Stock 03726CL10; 03726WH10; C04045CL; C04045WH

Numbers

Recommended use Refer to Technical Information
Uses advised against Refer to Technical Information

Manufacturer Contact

Address Soudal Accumetric

350 Ring Road

Elizabethtown, KY, 42701

USA

Phone Emergency Phone Fax

(270) 769-3385 (800) 424-9300 (270) 765-2412

CHEMTREC

Section 2. Hazards Identification

Classification EYE DAMAGE/IRRITATION - Category 2A

HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD -

Category 3

SENSITIZATION - SKIN - Category 1

SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2

Signal Word Warning

Pictogram



Hazard Statements Causes serious eye irritation

Harmful to aquatic life with long lasting effects

May cause an allergic skin reaction

May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

Response Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If on skin: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Read label before use.

Wash contaminated clothing before reuse.

Prevention Avoid breathing dust/fume/gas/mist/ vapors/spray.

Avoid release to the environment

Contaminated work clothing must not be allowed out of the workplace.

Do not breathe dust/fume/gas/mist/ vapors/spray.

Wash hands thoroughly after handling. Wear eye protection/face protection.

Wear protective gloves.

Storage N/A

Disposal Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

Additional Information None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
1760-24-3	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	1% - 5%
2224-33-1	Vinyl Oximino Silane	1% - 5%
22984-54-9	Methyl Oximino Silane	1% - 5%
63148-62-9	Dimethylpolysiloxane	10% - 30%
112945-52-5	Amorphous fumed silica	5% - 10%
64741-44-2	Distillates (petroleum), straight-run middle	5% - 10%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Eve Contact Immediately flush with water for 15 minutes.

Skin Contact Remove from skin and immediately flush with water for 15 minutes. Get

medical attention if irritation or ill effects develop or persist.

Inhalation Remove to fresh air. If symptoms persist, obtain appropriate medical attention.

Get medical attention. Ingestion

Comments Treat according to person's condition and specifics of exposure.

Section 5. Fire Fighting Measures

Suitable Extinguishing

Media

Carbon dioxide, dry chemcial, foam, water, water fog or spray

Unsuitable Extinguishing

Media

None known

Auto-ignition Temperature Not determined Lower Explosive Limit (%) Not applicable Upper Explosive Limit (%) Not applicable

Special Fire Fighting

Procedures

Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to

keep fire exposed containers cool.

Unusual Fire or Explosion None known

Hazards

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Section 7. Handling and Storage

Storage Keep container closed and store in a cool, well ventilated area, away from water or moisture.

Handling Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container

closed. Do not take internally. Use reasonable care.

Section 8. Exposure Controls/Personal Protection

Occupati	onal	Exposure
Limits		

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
N-beta-(aminoethyl)-gamma- aminopropyltrimethoxysilane	N/A	N/A	N/A
Vinyl Oximino Silane	N/A	N/A	N/A
Methyl Oximino Silane	N/A	N/A	N/A
Dimethylpolysiloxane	N/A	N/A	N/A
Amorphous fumed silica	10 mg/m3	6 mg/m3	N/A
Distillates (petroleum), straight-run middle	N/A	N/A	N/A

Personal Protective Equipment Goggles

Component Exposure Limits

Methyl ethyl ketoxime is formed upon contact with water or moisture in the air. Provide adequate ventilation to control exposures to within the exposure

guideline of 2 ppm (TWA).

Engineering Controls

Local Ventilation: Recommended General Ventilation: Recommended

Respiratory Protection

Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.

Suitable Respirator:

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits as determined by air sampling or are unknown, appropriate respiratory protection should be worn. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

Eye Protection
Skin Protection

Use proper protection - safety glasses as a minimum.

Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before

reuse. Chemical protective gloves are recommended.

Suitable Gloves: Silver Shield® 4H®

Comment

Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control methyl ethyl ketoxime

within the exposure guidelines or use respiratory protection.

Section 9. Physical and Chemical Properties

Physical State	Paste
Privsical State	Pasie

Color	Refer to product label
Odor	Slight
Odor Threshold	N/A
Solubility	Insoluble
Partition coefficient Water/n-octanol	N/A
VOC%	26 g/l (<3%)
Viscosity	850,000 cPs
Specific Gravity	1.03
Density Ibs/Gal	8.55
Pounds per Cubic Foot	N/A
Flash Point	Not
	determined
FP Method	N/A
Ph	Not
	applicable
Melting Point	Not
	determined
Boiling Point	Not
	determined
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not
	determined
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not
	determined
Vapor Density	Not
	determined

Note The above information is not intended for use in preparing product

specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

Conditions to Avoid None known Hazardous polymerization Will not occur

Materials to Avoid / Oxidizing material can cause a reaction. Incompatibility

Chemical Stability Stable

Section 11. Toxicological Information

Special Hazard Information Methyl Oximino Silane (22984-54-9) Possible skin sensitizer

on Component Vinyl Oximino Silane (2224-33-1) Possible skin sensitizer

Component Toxicology Methyl Ethyl Ketoxime (MEKO) is formed upon contact with water or humid air.

Male rodents exposed to MEKO vapor throughout their lifetime developed liver

Male rodents exposed to MEKO vapor throughout their lifetime developed liver tumors. Since many commonly used chemicals cause liver tumors in rats and mice, additional testing is planned by the MEKO supplier to determine any relevance to humans. Until more data is known, exposure levels should be

maintained as low as achievable.

Carcinogenicity No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Mutagenicity This product is not known to be a mutagen. Teratogenicity This product is not known to be teratogenic.

Reproductive Toxin This product is not known to be a reproductive toxin.

Section 12. Ecological Information

Environmental Effects Complete information is not yet available. Fate and Effects in Waste Complete information is not yet available.

Water Treatment Plants

Environmental Fate and Constribution

Complete information is not yet available.

Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this

product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the

requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number N/A

UN Proper Shipping Name Not regulated DOT Classification Not regulated Packing Group Not regulated

Air Shipment (IATA) Not subject to IATA regulations.

Ocean Shipment (IMDG) Not subject to IMDG code.

Section 15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication

Standard 29 CFR 1910.1200.

TSCA Status All chemical substances found in this product comply with the Toxic

Substances Control Act inventory reporting requirements.

SARA Title III Section 302

Extremely Hazardous

Substances

SARA Titre III Section 304

CERCLA Substances

dangereuses

SARA Title III Section

311/312

SARA Title III Section 313

Toxic Chemicals

California Proposition 65

No components subject to 40 CFR 370

None present or none present in regulated quantities.

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:

None known

None

None

Section 16. Other Information

Revision Date 11/10/2015

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with

the use of the material or the results to be obtained from the use thereof.