# Safety Data Sheet

#### **BOSS® 9101, 91010 Cyanoacrylate Adhesive**

#### Section 1. Identification

Product Identifier BOSS® 9101, 91010 Cyanoacrylate Adhesive

Synonyms 04239CL10 Manufacturer Stock 04239CL10

Numbers

Recommended use
Uses advised against

Refer to Technical Data Refer to Technical Data

Manufacturer Contact

Address

SOUDAL Accumetric 350 Ring Road

Elizabethtown, KY, 42701

USA

Phone Emergency Phone Fax (270) 769-3385 (800) 424-9300 N/A

(270) 769-3385 (800) 424-930 Chemtrec CHEMTREC

#### Section 2. Hazards Identification

Classification EYE DAMAGE/IRRITATION - Category 2A

FLAMMABLE LIQUIDS - Category 4

SKIN CORROSION/IRRITATION - Category 2

SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3

Signal Word Warning

**Pictogram** 

Hazard Statements Causes serious eye irritation

Causes skin irritation Combustible liquid

May cause respiratory irritation.

**Precautionary Statements** 

Response Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If on skin: Wash with plenty of water.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Specific treatment (refer to product label)

Take off contaminated clothing and wash it before reuse.

Prevention Avoid breathing dust/fume/gas/mist/ vapors/spray.

Keep away from heat.

Use only outdoors or in a well-ventilated area.

Wash thoroughly after handling. Wear eye protection/face protection.

Wear protective gloves.

Wear protective gloves/eye protection/face protection

Storage Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national

/international regulations.

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

Additional Information None known

## Section 3. Ingredients

| CAS       | Ingredient Name       | Weight %   |
|-----------|-----------------------|------------|
| 7085-85-0 | Ethyl-2-Cyanoacrylate | 50% - 100% |

Occupational exposure limits, if available, are listed in Section 8.

#### **Section 4. First-Aid Measures**

Skin Contact Soak in warm water. Do not pull skin apart. See supplemental section for

emergency action.

Inhalation Remove to fresh air. If symptoms persist, obtain appropriate medical attention.

Ingestion Ingestion is unlikely. See supplemental section for emergency action.

Eye Contact Flush with warm water. If eyelids are bonded closed, release eyelashes with

warm water by covering the eye with a wet pad. Do not force eye open. See

supplemental section for emergency action.

First Aid Supplement Cyanoacrylate adhesive is a very fast setting and strong adhesive. It bonds to

human tissue and skin in seconds. Experience has shown that accidents due

to Cyanoacrylates are best handles by passive, non-surgical first aid. Treatment of specific types of accidents are suggested as follows:

Skin Contact Remove excess adhesive. Soak in warm, soapy water. The adhesive will

come loose from the skin in several hours. Dried adhesive does not present a health hazard even when bonded to the skin. Avoid contact with clothes,

fabrics, rags, or tissue. Contact with these materials may cause

polymerization. The polymerization of large amounts of adhesive will generate heat causing smoke, skin burns, and strong, irritating vapors. Wear rubber or polyethylene gloves and an apron when handling large amounts of adhesive.

Skin Adhesion First immerse the bonded surfaces in warm, soapy water. Peel off or roll the

surfaces open with the end of a blunt edge, such as a spatula or a spoon handle, then remove adhesive with soap and water. Do not try to pull the

surfaces apart with a direct opposing action.

throughly with warm water and apply a gauze patch. The eye will open without further action, typically in one to two days. There will be no residual damage.

Do not try to pull the surfaces apart with a direct opposing action.

Adhesive in eye Adhesive introduced into the eyes will attach itself to the eye protein and will

disassociate from it over intermittent periods, usually several hours. This will cause periods of weeping until clearance is achieved. It is important to understand that disassociation will normally occur within a matter of hours,

even with gross contamination.

Mouth If lips are accidentally stuck together apply lots of warm water and encourage

maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action. It is almost impossible to swallow cyanoacrylate. The adhesive solidifies and adheres in

the mouth. Saliva will lift the adhesive in one to two days.

Burns Cyanoacrylate gives off heat on solidification. In rare cases, large drops will

increase in temperature enough to cause a burn. Burns should be treated normally after the lump of cyanoacrylate is released from the tissue as

described above.

Surgery It should never be necessary to use such drastic action to separate

accidentally bonded skin.

#### Section 5. Fire Fighting Measures

Suitable Extinguishing N

N/A

Media

N/A

Unsuitable Extinguishing Media

I W/A

Extinguishing Media

Carbon Dioxide, Dry Chemical, Foam

Unusual Fire or Explosion N

None known

Hazards

Special Fire Fighting

Wear self- contained breathing apparatus.

**Procedures** 

#### Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Observe all personal protection equipment recommendations. Do not use cloths for clean up. Flood spilled material with water to polymerize. Cured material can be scrapped up and disposed of as nonhazardous waste. Make sure spill area is well ventilated.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable.

# Section 7. Handling and Storage

Storage Store away from heat and direct sunlight to maximize shelf life. Store inside in

a dry location. Keep container tightly closed.

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapor or mist. Avoid

contact with paper goods or fabric. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors.

#### Section 8. Exposure Controls/Personal Protection

| Occupational Exposure Limits | Ingredient Name       | ACGIH TLV | OSHA PEL | STEL |
|------------------------------|-----------------------|-----------|----------|------|
|                              | Ethyl-2-Cyanoacrylate | 0.2 ppm   | None     | N/A  |

Personal Protective

Goggles, Gloves

Equipment Eye Protection

Skin Protection

Safety goggles or glasses with side shields are recommended. Polyethylene or non-reactive gloves. Do not use cotton, PVC or wool.

Ventilation Respiratory Protection

Local exhaust ventilation is recommended to maintain vapor level below TLV. Not applicable with good local exhaust. Use NIOSH approved respirator if

there is a potential to exceed exposure limits.

#### Section 9. Physical and Chemical Properties

| Liquid         |  |  |
|----------------|--|--|
| Colorless      |  |  |
| Characteristic |  |  |
| Not            |  |  |
| determined     |  |  |
| Polymerized    |  |  |
| by water       |  |  |
| Not            |  |  |
| determined     |  |  |
| < 20 g/L       |  |  |
| (estimated)    |  |  |
| Not            |  |  |
| determined     |  |  |
| 1.05           |  |  |
|                |  |  |

| Density lbs/Gal           | 8.762          |
|---------------------------|----------------|
| Pounds per Cubic Foot     | N/A            |
| Flash Point               | 87C 189F       |
| FP Method                 | N/A            |
| Ph                        | Not            |
|                           | determined     |
| Melting Point             | Undetermined   |
| Boiling Point             | >150C >302F    |
| Boiling Range             | N/A            |
| LEL                       | N/A            |
| UEL                       | N/A            |
| Evaporation Rate          | Not            |
|                           | determined     |
| Flammability              | Not applicable |
| Decomposition Temperature | Not            |
|                           | determined     |
| Auto-ignition Temperature | Product is not |
|                           | self igniting  |
| Vapor Pressure            | 0.3 hPa        |
| Vapor Density             | Not            |
|                           | determined     |

Note The above information is not intended for use in preparing product

specifications. Contact SOUDAL Accumentric before writing specifications.

#### Section 10. Stability and Reactivity

Chemical Stability Stable under recommended storage conditions.

Hazardous Polymerization Rapid exothermic polymerization will occur in the presence of water, amines,

alkalis and alcohols.

Materials to Avoid / Incompatibility

Polymerized by contact with water, alcohols, amines, and alkalis.

## Section 11. Toxicological Information

Special Hazard Information No known applicable information.

on Components

Component Toxicology

Information

No known applicable information.

#### Section 12. Ecological Information

Fate and Effects in Waste Complete information is not yet available.

Water Treatment Plants

Environmental Effects Complete information is not yet available. Environmental Fate and Complete information is not yet available.

Distribution

#### Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this

product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the

requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

#### Section 14. Transport Information

**UN Number** N/A UN Proper Shipping Name N/A **DOT Classification** N/A

N/A **Packing Group** 

Air Shipment (IATA) Not subject to IATA regulations. Not subject to IMDG code. Ocean Shipment (IMDG) Road Shipment Not subject to DOT regulations.

Information (DOT)

#### Section 15. Regulatory Information

None known Pennsylvania **New Jersey** None known

Massachusetts No ingredient regulated by MA Right-to-Know Law present.

California Proposition 65 This product contains the following chemical(s) listed by the State of California

> under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:

Saccharin. Proper usage necessitates no Proposition 65 warning.

SARA Title III Section 313

**Toxic Chemicals** 

None present or none present in regulated quantities.

SARA Title III Section 312

**Hazard Class** 

Acute: Yes Chronic: Yes Fire: Yes Pressure: No

Reactive: Yes

None

SARA Titre III Section 304 None

**CERCLA Substances** 

dangereuses

SARA Title III Section 302

**Extremely Hazardous** 

Substances

**TSCA Status** All chemical substances found in this product comply with the Toxic

Substances Control Act inventory reporting requirements.

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

## Section 16. Other Information

**Revision Date** 

6/5/2015

Disclaimer

The data contained herein is based upon information that SOUDAL Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.