



Safety Data Sheet

BOSS® 337 Construction Adhesive Foam Gun Grade

Section 1. Identification

Product Identifier	BOSS® 337 Construction Adhesive Foam Gun Grade		
Synonyms	33724; 04406TN10		
Manufacturer Stock Numbers	04406TN10		
Recommended use	Refer to Technical Information		
Uses advised against	Refer to Technical Information		
Manufacturer Contact Address	Soudal Accumetric 350 Ring Road Elizabethtown, KY, 42701 USA		
	Phone	Emergency Phone	Fax
	(270) 769-3385	(800) 424-9300 CHEMTREC	(270) 765-2412

Section 2. Hazards Identification

Classification	ACUTE TOXICITY - DERMAL - Category 4 ACUTE TOXICITY - INHALATION - Category 4 ACUTE TOXICITY - ORAL - Category 4 CARCINOGENICITY - Category 2 EYE DAMAGE/IRRITATION - Category 2A FLAMMABLE AEROSOLS - Category 1 SENSITIZATION - RESPIRATORY - Category 1A SENSITIZATION - SKIN - Category 1 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3
Signal Word	Danger

Pictogram



Hazard Statements

Causes serious eye irritation
Causes skin irritation
Extremely flammable aerosol
Harmful if inhaled
Harmful if swallowed
Harmful in contact with skin
May cause allergy or asthma symptoms or breathing difficulties if inhaled
May cause an allergic skin reaction
May cause damage to organs through prolonged or repeated exposure (respiratory tract).
May cause respiratory irritation.
Suspected of causing cancer.

Precautionary Statements

Response

Call a poison center/doctor if you feel unwell.
Get medical advice/attention if you feel unwell.
If experiencing respiratory symptoms: Call a poison center/doctor.
If exposed or concerned: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
If on skin: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
If swallowed: Call a poison center/doctor if you feel unwell.
Read label before use. If medical advice is needed, have product container or label at hand.
Rinse mouth.
Take off contaminated clothing and wash it before reuse.
Wash contaminated clothing before reuse.

Prevention

Avoid breathing dust/fume/gas/mist/ vapors/spray.
Contaminated work clothing must not be allowed out of the workplace.
Do not eat, drink or smoke when using this product.
Do not handle until all safety precautions have been read and understood.
Do not spray on an open flame or other ignition source.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Obtain special instructions before use.
Pressurized container: Do not pierce or burn, even after use.
Use only outdoors or in a well-ventilated area.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
Wear respiratory protection.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Disposal Dispose of contents/container to in accordance with local/regional/national /international regulations.

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

Other Hazards Contains isocyanates. See information supplied by the manufacturer. Allergic sensitization may be possible with isocyanates. Persons already sensitized to diisocyanates may develop allergic reactions when using this product.

Section 3. Ingredients

CAS	Ingredient Name	Weight %
6425-39-4	Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis-	< 1 %
75-28-5	Isobutane	< 10 %
9016-87-9	Polymeric diphenylmethane diisocyanate	> 25 %
	Copolymer	1% - 5%
74-98-6	Propane	1% - 5%
115-10-6	Dimethyl ether	10% - 15%
8001-20-5	Tung oil	10% - 15%
13674-84-5	Trichorylpropylene Phosphate	25% - 30%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Description of necessary measures IF exposed or concerned: Get medical advice/attention; Call a POISON CENTER or doctor/physician. Get medical advice/attention if you feel unwell.

Inhalation IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician. Specific treatment (see label). If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms:

Skin IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor/physician if you feel unwell. Specific treatment (see ... on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.

Eyes IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.

Indication of any immediate medical attention and special treatment needed Treat symptomatically and supportively. Persons already sensitized to diisocyanates may develop allergic reactions when using this product.

Most Important
Symptoms/Effects

Acute
Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

Delayed
May cause allergic or asthmatic symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure: respiratory tract.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Water, carbon dioxide
Unsuitable Extinguishing Media	None known
Special Hazards Arising from the Chemical	Extremely flammable aerosol.
Hazardous Combustion Products	Oxides of carbon, Phosphorus oxides, hydrogen cyanide, hydrogen chloride. May polymerize when heated.
Special Protective Equipment and Precautions for Firefighters	Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Do not spray on an open flame or other ignition sources. Do not pierce or burn, even after use. Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.
Fire Fighting Measures	Danger of explosion. Keep unnecessary people away, isolate hazard area and deny entry. Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. Do not allow to enter into surface water or drains.

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures	Wear appropriate personal protective equipment recommended in Section 8 of the SDS. Do not smoke when using this product or handle near an open flame or sparks. Use explosion-proof electrical/ventilating/lighting equipment.
Methods and Materials for Containment and Cleaning Up	Do not pierce or burn, even after use.
Environmental Precautions	Do not allow to enter into surface water or drains. Dike for later disposal.

Section 7. Handling and Storage

Precautions for Safe Handling	Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Do not spray on an open flame or other ignition sources. Do not pierce or burn, even after use. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Wear protective gloves/clothing and eye/face protection. Take off contaminated clothing and wash before re-use. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Obtain special instructions before use. Do not handle until all
-------------------------------	--

Conditions for Safe Storage, Including any Incompatibilities

safety precautions have been read and understood. Use explosion-proof electrical/ventilating/lighting equipment.

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Ensure adequate ventilation of the storage area. Maximum storage period (time): 1 year.

Incompatible Materials

Heat, strong acids, strong bases, Amines. Keep away from all ignition sources.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis-	N/A	N/A	N/A
Isobutane	1000 ppm	N/A	1000 ppm
Polymeric diphenylmethane diisocyanate	0.005 ppm	0.02 mg/m ³	N/A
Copolymer	N/A	N/A	N/A
Propane	1000 ppm TWA	1000 ppm PEL	N/A
Dimethyl ether	N/A	400 ppm	N/A
Tung oil	N/A	N/A	N/A
Trichorylpropylene Phosphate	N/A	N/A	N/A

Personal Protective Equipment

Goggles, Gloves

Component Exposure Limits

Propane (74-98-6)

ACGIH:
1000 ppm TWA

NIOSH:
1000 ppm TWA; 1800 mg/m³TWA
2100 ppmIDLH (10% LEL)

OSHA (US):
1000 ppmTWA; 1800 mg/m³TWA

Isobutane (75-28-5)

ACGIH:
1000 ppm STEL

NIOSH:
800 ppmTWA; 1900 mg/m³TWA

Dimethyl ether (115-10-6)
Europe:

Biological limit value	1000 ppm TWA; 1920 mg/m3 TWA
Engineering Controls	There are no biological limit values for any of this product's components. Use explosion-proof electrical/ventilating/lighting equipment. Keep away from heat/sparks/open flames/hot surfaces.
Individual Protection Measures, such as Personal Protective Equipment	Eye/face protection Wear splash resistant safety goggles. Skin Protection Wear suitable protective clothing and gloves. Respiratory Protection Use a respirator with an organic vapor cartridge for concentrations exceeding the occupational exposure limit. Glove Recommendations Recommended material type: LOW DENSITY POLYETHYLENE

Section 9. Physical and Chemical Properties

Physical State	Aerosol
Color	Champagne
Odor	Characteristic
Odor Threshold	Not available
Solubility	Soluble in organic solvents
Partition coefficient Water/n-octanol	Not available
VOC%	N/A
Viscosity	Not available
Specific Gravity	0.95
Density lbs/Gal	7.928
Pounds per Cubic Foot	59.307
Flash Point	Not available
FP Method	N/A
Ph	Not available
Melting Point	Not available
Boiling Point	Not available
Boiling Range	Not available
LEL	N/A
UEL	N/A
Evaporation Rate	Not available
Flammability	Not available
Decomposition Temperature	Not available
Auto-ignition Temperature	Not available
Vapor Pressure	Not available
Vapor Density	Not available

Note The above information is not intended for use in preparing product

specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

Reactivity	May polymerize when heated.
Chemical Stability	Stable under normal conditions of use.
Possibility of Hazardous Reactions	May polymerize when heated.
Conditions to Avoid	Avoid contact with incompatible materials. Keep away from heat/sparks/open flame/hot surfaces - No smoking. Do not spray on an open flame or other ignition sources. Do not pierce or burn, even after use.
Incompatible Materials	Heat, strong acids, strong bases, Amines, Keep away from all ignition sources.
Hazardous decomposition products	Oxides of carbon, Phosphorus oxides, hydrogen cyanide, hydrogen chloride.

Section 11. Toxicological Information

Information on Likely Routes of Exposure	Inhalation Harmful if inhaled. May cause allergic or asthmatic symptoms or breathing difficulties if inhaled. May cause respiratory irritation.
	Skin Contact Harmful in contact with skin. Causes skin irritation. May cause allergic skin reaction.
Component Analysis - LD50/LC50	Eye Contact Causes serious eye damage.
	Ingestion Harmful if swallowed.
	The components of this material have been reviewed in various sources and the following selected endpoints are published: 2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5) Oral LD50Rat 500 mg/kg Dermal LD50Rabbit 1230 mg/kg Inhalation LC50Rat 5 mg/L 4 h
	Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) Inhalation LC50Rat 490 mg/m ³ 4 h
	Propane (74-98-6) Inhalation LC50Rat 658 mg/L 4 h
	Isobutane (75-28-5) Inhalation LC50Rat 658 mg/L 4 h
	Dimethyl ether (115-10-6) Inhalation LC50Rat 308.5 mg/L 4 h

Acute and Chronic Toxicity	<p>Immediate Effects Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergic or asthmatic symptoms or breathing difficulties if inhaled. May cause respiratory irritation.</p> <p>Delayed Effects Suspected of causing cancer. May cause allergic skin reaction. May cause damage to organs through prolonged or repeated exposure: respiratory tract.</p>
Irritation/Corrosivity Data	Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.
Respiratory Sensitization	May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.
Dermal Sensitization	May cause allergic skin reaction.
Component	Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)
Carcinogenicity	<p>IARC: Supplement 7 [1987]; Monograph 19 [1979](Group 3 (not classifiable))</p> <p>DFG: Category 4 (no significant contribution to human cancer)</p>
Germ Cell Mutagenicity	No data available
Reproductive Toxicity	No data available
Specific Target Organ Toxicity	<p>Single Exposure: respiratory tract.</p> <p>Repeated Exposure: respiratory tract.</p>
Aspiration Hazard	No data available
Medical Conditions Aggravated by Exposure	eye disorders, respiratory disorders, skin disorders, gastrointestinal disorders; May produce an allergic reaction. Persons already sensitized to diisocyanates may develop allergic reactions when using this product.

Section 12. Ecological Information

Component Analysis - Aquatic Toxicity	<p>2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)</p> <p>Fish: LC50 96 h Brachydanio rerio 56.2 mg/L [static]; LC50 96 h Pimephales promelas 98 mg/L [static]; LC50 96 h Poecilia reticulata 30 mg/L [static]</p> <p>Algae: EC50 72 h Desmodesmus subspicatus 45 mg/L IUCLID; EC50 96 h Pseudokirchneriella subcapitata 4 mg/L IUCLID</p> <p>Invertebrate: EC50 48 h Daphnia magna 63 mg/L IUCLID</p>
Bioaccumulation	No information available.
Mobility	No information available.
Biodegradation	Contains non readily biodegradable component(s).

Section 13. Disposal

Disposal Methods	Dispose of contents/container in accordance with local/regional/national/international regulations. Do not allow to enter into ground-water, surface water or drains.
------------------	---

Section 14. Transport Information

UN Number 1950
UN Proper Shipping Name Aerosols
DOT Classification Hazard Class: 2.2 Required Label(s): 2.2
Packing Group None assigned

Section 15. Regulatory Information

U.S. Federal Regulations This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)

SARA 313: 1 % de minimis concentration

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: Yes Reactivity: Yes

U.S. State Regulations The following components appear on one or more of the following state hazardous substances lists:

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)

NJ

Propane (74-98-6)

MA, MN, NJ, PA

Isobutane (75-28-5)

MA, NJ, PA

Dimethyl ether (15-10-6)

MA, MN, NJ, PA

Not listed under California Proposition 65

Canadian WHMIS Ingredient Disclosure List (IDL) Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on SDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL:

Castor oil (8001-79-4) 1 %

WHMS Classification B5, D2A, D2B

Section 16. Other Information

Revision Date 8/12/2016

HMIS and NFPA Rating HMIS
Health: 2*
Fire: 3
Reactivity: 3

NFPA
Health: 2
Fire: 3
Reactivity: 3

Hazard Scale:

0 = Minimal

1 = Slight

2 = Moderate

3 = Serious

4 = Severe

* = Chronic hazard

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.