

# Safety Data Sheet

### **BOSS® 315 RTV 100% Silicone Sealant**

### **Section 1. Identification**

Product Identifier BOSS® 315 RTV 100% Silicone Sealant

Synonyms 31590; 31560; 31530; 31531; 31532; 31520; 31521; 31503; 31502; 31500;

31501; 31551; 31573; 31572; 31570; 31571; 01004CL84; 01003CL84;

01000CL72; 01000WH72; 01000BK72; 01000CL12; 01011AL48; 01011AL48; 01011BK48; 01011CL48; 01011WH48; 01300WH05; 01048AL01; 01048BK01;

01048CL01; 01048WH01; 01000WH12

Manufacturer Stock

Numbers

 $01004CL84;\ 01003CL84;\ 01000CL72;\ 01000WH72;\ 01000BK72;\ 01000CL12;$ 

01011AL48; 01011BK48; 01011CL48; 01011WH48; 01300WH05; 01048AL01;

01048BK01; 01048CL01; 01048WH01; 01000WH12

Recommended use

Uses advised against

Refer to Technical Information

Refer to Technical Information

Manufacturer Contact

Address

Soudal Accumetric 350 Ring Road

Elizabethtown, KY, 42701

**USA** 

Phone

**Emergency Phone** 

Fax

(270) 769-3385

(800) 424-9300

(270) 765-2412

CHEMTREC

### Section 2. Hazards Identification

Classification

N/A

Signal Word

Pictogram

Hazard Statements

N/A

**Precautionary Statements** 

Response N/A

Prevention Use only outdoors or in a well-ventilated area.

N/A Storage N/A Disposal

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

Hazard classification This material is not hazardous under the criteria of the Federal OSHA Hazard

Communication Standard 29CFR 1910.1200.

Other hazards None known

### **Section 3. Ingredients**

| CAS     | Ingredient Name                                    | Weight % |
|---------|--|----------|
| Mixture | Contains no hazardous ingredients according to GHS | 100 %    |

Occupational exposure limits, if available, are listed in Section 8.

### **Section 4. First-Aid Measures**

Description of first aid measures

General advice:

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation

Move person to fresh air; if effects occur, consult a physician.

Skin contact

Wash off with plenty of water.

Eye contact

Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion

No emergency medical treatment necessary.

Most important symptoms delayed

Aside from the information found under Description of first aid measures (above) and effects, both acute and and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate Notes to physician

medical attention and special treatment needed

No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

### Section 5. Fire Fighting Measures

Suitable Extinguishing

Media

Water spray, Alcohol-resistant foam, Carbon dioxide (CO2), Dry chemical

Unsuitable Extinguishing

Media

None known

Special hazards arising from the substance or mixture

Hazardous combustion products Carbon oxides Silicon oxides

Unusual Fire and Explosion Hazards

Exposure to combustion products may be a hazard to health.

Advice for firefighters

Fire Fighting Procedures

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate

area.

Special protective equipment for firefighters

Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

### Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

See sections: 7, 8, 11, 12 and 13.

### Section 7. Handling and Storage

Precautions for safe handling

Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation. See Engineering measures under

EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage Keep in properly labeled containers. Store in accordance with the particular national regulations.

> Do not store with the following product types: Strong oxidizing agents.

Unsuitable materials for containers:

None known.

### **Section 8. Exposure Controls/Personal Protection**

| Occupational Exposure Limits     | Ingredient Name                                    | ACGIH<br>TLV | OSHA<br>PEL | STEL |
|----------------------------------|--|--------------|-------------|------|
|                                  | Contains no hazardous ingredients according to GHS | 5 mg/m≈      | 5 mg/m≈     | N/A  |
| Personal Protective<br>Equipment | Goggles  |              |             |      |
|                                  |  |              |             |      |

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

Exposure controls

Engineering controls:

Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection

Use safety glasses (with side shields).

Skin protection Hand protection

Chemical protective gloves should not be needed when handling this material. Consistent with general hygienic practice for any material, skin contact should be minimized.

Other protection

No precautions other than clean body-covering clothing should be needed.

Respiratory protection

Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated

temperatures without sufficient ventilation, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

## Section 9. Physical and Chemical Properties

| Physical State                        | Paste                |  |
|---------------------------------------|----------------------|--|
| Color                                 | Refer to             |  |
|                                       | product label        |  |
| Odor                                  | Acetic Acid          |  |
| Odor Threshold                        | No data              |  |
|                                       | available            |  |
| Solubility                            | No data              |  |
|                                       | available            |  |
| Partition coefficient Water/n-octanol | No data              |  |
|                                       | available            |  |
| VOC%                                  | 23 g/L               |  |
| Viscosity                             | Not                  |  |
|                                       | applicable           |  |
| Specific Gravity                      | 1.007                |  |
| Density lbs/Gal                       | N/A                  |  |
| Pounds per Cubic Foot                 | N/A                  |  |
| Flash Point                           | >212F                |  |
|                                       | >100C                |  |
| FP Method                             | Closed Cup           |  |
| рН                                    | Not                  |  |
|                                       | applicable           |  |
| Melting Point                         | No data              |  |
|                                       | available            |  |
| Boiling Point                         | Not                  |  |
|                                       | applicable           |  |
| Boiling Range                         | Not                  |  |
|                                       | applicable           |  |
| LEL                                   | N/A                  |  |
| UEL                                   | N/A                  |  |
| Evaporation Rate                      | Not                  |  |
|                                       | applicable           |  |
| Flammability                          | Not                  |  |
|                                       | classified as        |  |
|                                       | a                    |  |
|                                       | flammability         |  |
| Decemberation Temperature             | hazard               |  |
| Decomposition Temperature             | No data<br>available |  |
| Auto ignition Tomporeture             |                      |  |
| Auto-ignition Temperature             | No data<br>available |  |
|                                       | avaliable            |  |

| Vapor Pressure | Not        |
|----------------|------------|
|                | applicable |
| Vapor Density  | No data    |
|                | available  |

Note

The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

### Section 10. Stability and Reactivity

Reactivity Not classified as a reactivity hazard.

Chemical stability Stable under normal conditions.

Possibility of hazardous Can react with strong oxidizing agents. When heated to temperatures above 150 reactions

°C (300 °F) in the presence of air, trace quantities of formaldehyde may be

released. Adequate ventilation is required.

Conditions to avoid None known

Incompatible materials Oxidizing agents

Hazardous decomposition Formaldehyde

products

Acute toxicity

## Section 11. Toxicological Information

Toxicological information appears in this section when such data is available.

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s): LD50, Rat, > 5,000 mg/kg Estimated.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s): LD50, Rabbit, > 2,000 mg/kg Estimated.

Acute inhalation toxicity

Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.

As product: The LC50 has not been determined.

Prolonged exposure not likely to cause significant skin irritation.

May cause slight temporary eye irritation.

Corneal injury is unlikely.

May cause mild eye discomfort.

Skin corrosion/irritation Serious eye damage/eye irritation

Sensitization For skin sensitization:

Contains component(s) which did not cause allergic skin sensitization in guinea

pigs.

For respiratory sensitization:

No relevant information found.

Specific Target Organ Systemic Toxicity Single Exposure

Evaluation of available data suggests that this material is not an STOT-SE

toxicant.

Repeated Exposure

For the major component(s): Based on available data, repeated exposures are

not anticipated to cause additional significant adverse effects.

Contains an additional component(s) that is/are encapsulated in the product

and are not expected to be released under normal processing conditions or

foreseeable emergency.

Carcinogenicity For this family of materials: Did not cause cancer in long-term animal studies

which used routes of exposure considered relevant to industrial handling.

Positive results have been reported in other studies using routes of exposure

not relevant to industrial handling.

Teratogenicity Contains component(s) which did not cause birth defects or any other fetal

effects in lab animals.

Reproductive toxicity Contains component(s) which did not interfere with reproduction in animal

studies.

Mutagenicity Contains a component(s) which were negative in in vitro genetic toxicity studies.

Contains component(s) which were negative in animal genetic toxicity studies.

Aspiration Hazard Based on physical properties, not likely to be an aspiration hazard.

### **Section 12. Ecological Information**

Ecotoxicological information appears in this section when such data is available.

Toxicity No data available.

Persistence and No data available.

degradability
Bioaccumulative potential No data available.

Mobility in soil No data available.

### Section 13. Disposal

Disposal methods DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF

WATER. All disposal practices must be in compliance with all Federal,

State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING

PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE

INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 15

Treatment and disposal methods of used packaging

Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

### **Section 14. Transport Information**

UN Number N/A

UN Proper Shipping Name Not regulated for transport

DOT Classification Not regulated for transport

Packing Group Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

### **Section 15. Regulatory Information**

SARA Sections 311 and No SARA Hazards

312 SARA Section 313

This material does not contain any chemical components with known CAS

numbers that exceed the threshold (De Minimis) reporting levels established by

SARA Title III, Section 313.

CERCLA Section 103 Calculated RQ exceeds reasonably attainable upper limit.

Components

Acetic acid (64-19-7) 5000 lbs RQ

Acetic anhydride (108-24-7) 5000 lbs RQ

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of

Pennsylvania law:

Polydimethylsiloxane hydroxy-terminated (70131-67-8)

Silicon dioxide (7631-86-9)

California Prop. 65 This product does not contain any chemicals known to State of California to

cause cancer, birth defects, or any other reproductive harm.

### Section 16. Other Information

#### HMIS and NFPA Rating

HMIS Health: 0 Fire: 1

Reactivity: 0

NFPA Health: 0 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal

1 = Slight

2 = Moderate

3 = Serious

4 = Severe

\* = Chronic hazard

#### Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.