

# BOSS<sup>®</sup> 334 Window & Door Minimal Expanding Genius Gun Foam

### TYPICAL PROPERTIES

Density.....	1.56 lbs./ft <sup>3</sup>
Thermal Conductivity .....	0.22 - 0.26 Btu-in/hr-F-ft <sup>2</sup>
R Value .....	3.8 - 4.8 per inch
Tack Free (1" bead).....	8 minutes (68°F & 65% RH)
Fully Cured (1" bead).....	12 hours (68°F & 65% RH)
Cutttable (1" bead) .....	1 hour (68°F & 65% RH)
Tensile Strength.....	15 psi
Shear Strength .....	7 psi
Elongation .....	20%
Yield/20 Oz. Can .....	6.6 gallons freely foamed
Theoretical Yield - 20 oz. 1/4" bead.....	2279 ft.
20 oz. 1/2" bead.....	577 ft.
VOC.....	175 g/l
Service Temperature.....	-40°F to 200°F
Application Temperature .....	40°F to 115°F

\*Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.



### FEATURES

- AAMA 812-04 approved
- CFC propellant free
- Excellent adhesion on most substrates (except Teflon, PE and PP)
- High thermal and acoustical insulation
- Very good filling capacities
- Excellent mounting capacities
- Excellent stability (no shrink or post expansion)
- Very precise application due to the foam gun system
- Low pressure build, reducing the chance of bowing
- VOC Compliant

### DESCRIPTION

**BOSS<sup>®</sup> 334** Window & Door Minimal Expanding Genius Gun Foam is a one-component, ready to use polyurethane foam, formulated to seal the gap around window and door frame and the rough opening. **BOSS<sup>®</sup> 334** expands to generate an effective seal, and when used properly is proven not to distort or bow window and door frames. **BOSS<sup>®</sup> 334** will achieve a Sound Transmission Class (STC) of 58 when applying it in accordance with ASTM C-919 "Standard Practice for use of Sealants in Acoustical Applications".

### USES

- Installing of window and door frames
- Filling of cavities
- Sealing of all openings in roof constructions
- Creation of a soundproof screen
- Mounting and sealing of window and door frames
- Connecting of insulation materials and roof constructions
- Application of a soundproofing layer on motors
- Improving thermal isolation in cooling systems

## HOW TO USE

Surfaces must be clean and free of grease and dust. Spray mist into cavity prior to applying foam and in between layers to improve adhesion and speed up curing. Shake can vigorously for 30 seconds before use and regularly during use for maximum yield. Can must be held **UPSIDE DOWN** during application. Flip open cap and wear gloves provided inside cap. Unclip nozzle. Point nozzle and press trigger. Fill void 50% full to allow for expansion. For best results, use in temperatures between 41°F to 95°F.

## DANGER!

**EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE.** Turn off all pilot lights, electrical igniters, burners and other sources of ignition or heat during use. Do not smoke, use matches or lighters while dispensing foam. Do not expose to direct sunlight, high heat or store in enclosed vehicle. Avoid breathing vapor/spray. Use only outdoors or in a well ventilated area with appropriate breathing apparatus. Avoid contact with skin and eyes. Wearing eyewear and gloves is recommended. Do not incinerate or puncture can. Store at temperatures below 120°F. **KEEP OUT OF REACH OF CHILDREN.** For safe handling information on this product, consult the Safety Data Sheet (SDS).

**FIRST AID:** In case of eye contact, flush immediately with water for 15 minutes and get medical help. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help. If swallowed, drink large quantities of water. DO NOT induce vomiting. GET PHYSICIAN ASSISTANCE IN ALL CASES. Cured foam is not harmful to health.

## CONTAINS

Polymethylenepolyphenylisocyanate, Dimethylether, Isobutane and Propane.

## SHIPPING LIMITATIONS

Ground shipments only. Cannot ship by air. Reactive VOC 175 g/l (18% wt)

## CLEAN UP

Uncured sealant can be easily removed using BOSS® 335 or a solvent such as alcohol or acetone. For an environmental and health friendlier choice use BOSS® Biggie Wipes. If the sealant is cured it must be removed mechanically by cutting and scraping.

## SPECIFICATIONS

<b>ASTM E-2112</b> - Standard practice for installation of exterior windows, doors and skylights (conform or results)	Conforms
<b>ASTM E-283</b> - Standard test method for determining rate of air leakage through exterior windows, curtain walls and doors under specified pressure differences across the specimen (conform or results)	Air leakage <0,01 cfm/ft <sup>2</sup> at 6.24 psf pressure (or 50mph wind speed) in 1 cm wide gap
<b>ASTM E-331</b> - (2009) Standard test method for water penetration of exterior windows, skylights, doors and curtain walls by uniform static air pressure difference (conform or results)	Conforms
<b>ASTM E-547</b> - (2009) Standard test method for water penetration of exterior windows, skylights, doors and curtain walls by cyclic static air pressure difference (conform or results)	No water leakage at 12 psf negative pressure
<b>ASTM C-1620</b> - Standard specification for aerosol polyurethane and aerosol latex foam sealants (conform or results)	Conforms
<b>ASTM E-84 UL 723</b>	Flame Spread 15 Smoke Developed 35
<b>AAMA 812</b> - 04 Voluntary practice for assessment of single component aerosol expanding polyurethane foams for sealing rough opening of fenestration installations	AAMA Tested and listed in the verified component list

## STORAGE AND SHELF LIFE

When stored upright in a dry environment at or below 70°F (21°C), **BOSS® 334** has a shelf life of 12 months from date of shipment. In countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the cap pointed upwards. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

## PACKAGING

**BOSS® 334** Window and Door Minimal Expanding Foam is available in 12 oz., 20 oz. and 24 oz. cans.

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning

the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non-warranty:** Because the storage, handling and application of the material is beyond Soudal Accumetric's control, we can accept no liability for the results obtained. Soudal Accumetric's sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Soudal Accumetric will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

MADE IN U.S.A.

## **BOSS® PRODUCTS**

**Soudal Accumetric**  
350 Ring Road / Elizabethtown, KY 42701 USA  
800-928-BOSS(2677)  
TEL (270)769-3385 / FAX (270)765-2412  
Outside U.S.  
TEL +1(270)769-3385 / FAX +1(270)765-2412  
[www.bossproducts.com](http://www.bossproducts.com)