

TECHNICAL DATA SHEET

DISC BRAKE QUIET PART NO. 49661

PHYSICAL PROPERTIES

Appearance	Red Paste
Odor	Acrylic
Flashpoint (TCC Method).....	None
Specific Gravity	1.0487
VOC %	Not Determined
VOC G/L	Not Determined
VOC Lbs./Gal.	Not Determined
Flammable	No
Plastic Safe	Not Determined
Evaporation Rate.....	Not Determined
DOT Proper Shipping Name.....	Not Regulated
VOC Compliant for CA & OTC ..	Not Regulated
Removal ... Remove with a degreaser or brake cleaner product	



DESCRIPTION

Dynatex® Disc Brake Quiet forms a water resistant, high-temperature film that absorbs noise while quieting squeaks and squeals. Specially formulated to dampen the vibrations that cause brake noise. For use on the back of non-shimmed disc pads.

FEATURES

- Compatible with anti-lock brake systems
- Eliminates disc brake squeal
- Protects against corrosion
- Allows for easy disassembly
- For use on all cars and trucks

TYPICAL APPLICATIONS

- Backing plates
- Brake pad contact points
- Disc brake pads
- Outboard and inboard pads for disc braking systems

TYPICAL CURING PERFORMANCE

Dynatex® Disc Brake Quiet should dry for a minimum of 10 minutes prior to reassembly. Full dry time is a minimum of three hours. Cure times will vary with temperature, humidity and gap.

DIRECTIONS

1. Remove the lug nuts holding the wheel assembly in place.
2. Remove the pins (or bolts) holding the caliper assembly to access the brake pad.
3. Clean the back side of brake pad with *Dynatex® Brake & Parts Cleaner (P/N 49665)* and wipe clean.
4. Apply a thin coat of Disc Brake Quiet to the back side of the disc pad.
5. Do not apply on the side that comes into contact with the rotor.
6. Allow to dry a minimum of 10 minutes.
7. Reassemble.

STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), *Dynatex® Disc Brake Quiet* has a shelf life of 12 months from date of shipment.

In Countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

Dynatex® A division of Soudal Accumetric

Dynatex

350 Ring Road
Elizabethtown
Kentucky 42701 USA
(800) 999-2937
TEL (270) 769-5557
FAX (270) 769-6418

Outside U.S.

TEL +1(270) 769-5557
FAX +1(270) 769-6418

Accumetric Asia Pacific, LTD

18 Kitpanit Bldg. 5th Floor
#502 Patpong Road
Suriyawong, Bangrak
Bangkok, 10500 Thailand
TEL (662) 634-3060
FAX (662) 634-3066

Email: sales@dynatexinc.com
Website: www.dynatexinc.com