

GASKET REMOVER PART NO. 49673

PHYSICAL PROPERTIES

Physical State.....	Liquid
Color/Appearance.....	Clear liquid
Odor.....	Ether-like
Specific Gravity.....	1.22
Boiling/Cond. Point.....	>100°F
Solubility.....	Soluble in water
pH.....	Not applicable
Evaporation Rate.....	>1 (BuAc=1)
VOC %.....	24%
Vapor Pressure.....	Not applicable
NFPA Flammability Rating.....	4*

*Highly Flammable

DESCRIPTION

Dynatex® Gasket Remover is an aerosol product designed to remove gasket residue from any type of metal or plastic housing. *Dynatex*® Gasket Remover quickly removes baked-on gaskets, silicone weatherstrip adhesive, carbon deposits, dried oil, adhesives, grease and paint. Removes gaskets in 10-12 minutes. Prepares metal parts for new gasket installation.

FEATURES

- Penetrates and cleans intricate shapes
- Eliminates excessive scraping and potential damage to flanged surfaces
- Saves time and labor
- Tested in accordance to 75/324/EEC Directive 6.1

TYPICAL APPLICATIONS

Dynatex® Gasket Remover Removes

- Baked-on gaskets and gasket cements
- Gaskets from small, difficult to reach areas
- Formed-in-place gaskets
- Gaskets from aluminum without scraping



DIRECTIONS FOR USE:

1. Provide adequate ventilation.
2. Protect painted and non-metal surfaces from overspray. The product will remove paint.
3. Shake can well. For best results, the aerosol can should be at room temperature before spraying.
4. Holding can 8 to 10 inches from surface to be coated, press nozzle and discharge the product onto the affected areas.
5. Allow to set for at least 15 minutes. Remove dissolved gasket with a plastic scraper and rages. Repeat if necessary.

GENERAL INFORMATION

This product is not recommended for use in pure oxygen environments and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet.

STORAGE AND SHELF LIFE

Dynatex® Gasket Remover should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building. Store in accordance with NFPA 30B for level 3 aerosol. *Dynatex® Gasket Remover* has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

TRANSPORTATION INFORMATION

DOT Road Shipment Information

DOT ClassificationHazardous
DOT Description...Consumer Commodity ORM-D
UN Number UN1950

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.



Dynatex
350 Ring Road
Elizabethtown
Kentucky 42701 USA
(800) 999-2937
TEL (270) 769-5557
FAX (270) 769-6418
Outside U.S.
TEL +1(270) 769-5557
FAX +1(270) 769-6418

Accumetric Asia Pacific, LTD
18 Kitpanit Bldg. 5th Floor
#502 Patpong Road
Suriyawong, Bangrak
Bangkok, 10500 Thailand
TEL (662) 634-3060
FAX (662) 634-3066

Email: sales@dynatexinc.com
Website: www.dynatexinc.com