



Safety Data Sheet

Dynatex® 47101 DynaCopper

Section 1. Identification

Product Identifier Dynatex® 47101 DynaCopper

Synonyms N/A

Manufacturer Stock Numbers N/A

Recommended use Refer to Technical Information

Uses advised against Refer to Technical Information

Manufacturer Contact

Address

Dynatex a division of Soudal Accumetric
350 Ring Road
Elizabethtown, KY, 42701
USA

Phone

(270) 769-3385

Emergency Phone

(800) 424-9300

CHEMTREC

Fax

(270) 769-6418

Section 2. Hazards Identification

Classification

EYE DAMAGE/IRRITATION - Category 2A
HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD -
Category 3
SENSITIZATION - SKIN - Category 1
SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2

Signal Word

Warning

Pictogram



Hazard Statements

Causes serious eye irritation
Harmful to aquatic life with long lasting effects
May cause an allergic skin reaction
May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

Response

Get medical advice/attention if you feel unwell.
If eye irritation persists: Get medical advice/attention.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If on skin: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Read label before use.
Wash contaminated clothing before reuse.

Prevention

Avoid breathing dust/fume/gas/mist/ vapors/spray.
Avoid release to the environment
Contaminated work clothing must not be allowed out of the workplace.
Do not breathe dust/fume/gas/mist/ vapors/spray.
Wash hands thoroughly after handling.
Wear eye protection/face protection.
Wear protective gloves.

Storage

N/A

Disposal

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Ingredients of unknown toxicity

0%

Hazards not Otherwise Classified

None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
112945-52-5	Amorphous fumed silica	5% - 10%
64741-44-2	Distillates (petroleum), straight-run middle	5% - 10%
63148-62-9	Dimethylpolysiloxane	10% - 30%
2224-33-1	Vinyl Oximino Silane	1% - 5%
22984-54-9	Methyl Oximino Silane	1% - 5%
1760-24-3	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	1% - 5%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Eye Contact	Immediately flush with water for 15 minutes.
Skin Contact	Remove from skin and immediately flush with water for 15 minutes. Get medical attention if irritation or ill effects develop or persist.
Inhalation	Remove to fresh air. If symptoms persist, obtain appropriate medical attention.
Ingestion	Get medical attention.
Comments	Treat according to person's condition and specifics of exposure.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.
Unsuitable Extinguishing Media	None known
Auto-ignition Temperature	Not determined
Flammability Limits in Air	Not determined
Special Fire Fighting Procedures	Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Unusual Fire or Explosion Hazards	None known

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release	Observe all personal protection equipment. Use absorbent material to collect and contain material for disposal. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.
---	--

Section 7. Handling and Storage

Storage	Keep container closed and store in a cool, well ventilated area, away from water or moisture.
Handling	Avoid breathing vapors in top of shipping container. Keep container closed. Use with adequate ventilation. Avoid contact with skin and clothing. Wash thoroughly

after handling.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Amorphous fumed silica	10 mg/m ³	6 mg/m ³	N/A
	Distillates (petroleum), straight-run middle	N/A	N/A	N/A
	Dimethylpolysiloxane	N/A	N/A	N/A
	Vinyl Oximino Silane	N/A	N/A	N/A
	Methyl Oximino Silane	N/A	N/A	N/A
	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	N/A	N/A	N/A
Personal Protective Equipment	N/A			
Component Exposure Limits	Methyl ethyl ketoxime is formed upon contact with water or moisture in the air. Provide adequate ventilation to control exposures to within the exposure guideline of 2 ppm (TWA).			
Engineering Controls	Local Ventilation: Recommended General Ventilation: Recommended			
Eye Protection	Use proper protection - safety glasses as a minimum.			
Skin Protection	Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.			
Respiratory Protection	Suitable Gloves: Silver Shield® 4H® Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls. Suitable Respirator: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits as determined by air sampling or are unknown, appropriate respiratory protection should be worn. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.			
Comment	Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control methyl ethyl ketoxime within the exposure guidelines or use respiratory protection.			

Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Copper

on Component

Vinyl Oximino Silane (2224-33-1) Possible skin sensitizer

Component Toxicology
Information

Methyl Ethyl Ketoxime (MEKO) is formed upon contact with water or humid air. Male rodents exposed to MEKO vapor throughout their lifetime developed liver tumors. Since many commonly used chemicals cause liver tumors in rats and mice, additional testing is planned by the MEKO supplier to determine any relevance to humans. Until more data is known, exposure levels should be maintained as low as achievable.

Carcinogenicity

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Mutagenicity

This product is not known to be a mutagen.

Teratogenicity

This product is not known to be teratogenic.

Reproductive Toxin

This product is not known to be a reproductive toxin.

Section 12. Ecological Information

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste
Water Treatment Plants

Complete information is not yet available.

Environmental Fate and
Distribution

Complete information is not yet available.

Section 13. Disposal

Waste Disposal Method

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number

N/A

UN Proper Shipping Name

Caulking & Glaziers, NOI

DOT Classification

None

Packing Group

N/A

Ocean Shipment (IMDG)

Not subject to IMDG code.

Section 15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status	All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.
SARA Title III Section 302 Extremely Hazardous Substances	None
SARA Titre III Section 304 CERCLA Substances dangereuses	None
SARA Title III Section 312 Hazard Class	Acute: Yes Chronic: Yes Fire: No Pressure: No Reactive: No
SARA Title III Section 313 Toxic Chemicals	None present or none present in regulated quantities.
Massachusetts	Silica, amorphous fumed (112945-52-5)
New Jersey	Silica, amorphous (112945-52-5) Dimethyl siloxane, hydroxy-terminated (70131-67-8) Polydimethylsiloxane (63148-62-9) Methyl tri (ethylmethylketoxime) silane (22984-54-9) Calcium carbonate, treated (1317-65-3) Vinyl oximino silane (2224-33-1)
Pennsylvania	Silica, amorphous (112945-52-5) Dimethyl siloxane, hydroxy-terminated (70131-67-8) Polydimethylsiloxane (63148-62-9) Methyl tri (ethylmethylketoxime) silane (22984-54-9) Calcium carbonate, treated (1317-65-3) Vinyl oximino silane (2224-33-1)
California Prop 65	WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the state of California to cause cancer and Methanol, which is known to the State of California to cause birth defects and other reproductive harm. For more information, go to www.P65Warnings.ca.gov .
Canada Domestic Substances List	All ingredients are listed on the DSL.

Section 16. Other Information

Revision Date 5/21/2018

Disclaimer The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.