



Safety Data Sheet

Dynatex® 47181 DynaGrey RTV Silicone Gasket Maker

Section 1. Identification

Product Identifier Dynatex® 47181 DynaGrey RTV Silicone Gasket Maker
Synonyms 47181GY12
Manufacturer Stock Numbers 47181GY12

Recommended use Refer to Technical Data
Uses advised against Refer to Technical Data

Manufacturer Contact
Address Dynatex a division of Soudal Accumetric
350 Ring Road
Elizabethtown, KY, 42701
USA

Phone	Emergency Phone	Fax
(270) 769-3385	(800) 424-9300 CHEMTREC	N/A

Section 2. Hazards Identification

Classification EYE DAMAGE/IRRITATION - Category 2A
HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD -
Category 3
SENSITIZATION - SKIN - Category 1
SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2

Signal Word Warning

Pictogram



Hazard Statements	Causes serious eye irritation Harmful to aquatic life with long lasting effects May cause an allergic skin reaction May cause damage to organs through prolonged or repeated exposure.
Precautionary Statements Response	Get medical advice/attention if you feel unwell. If eye irritation persists: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If on skin: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Read label before use. Wash contaminated clothing before reuse.
Prevention	Avoid breathing dust/fume/gas/mist/ vapors/spray. Avoid release to the environment Contaminated work clothing must not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/ vapors/spray. Wash hands thoroughly after handling. Wear eye protection/face protection. Wear protective gloves.
Storage	N/A
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Ingredients of unknown toxicity	0%
Hazards not Otherwise Classified	
Additional Information	None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
1760-24-3	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	1% - 5%
2224-33-1	Vinyl Oximino Silane	1% - 5%
22984-54-9	Methyl Oximino Silane	1% - 5%
63148-62-9	Dimethylpolysiloxane	10% - 30%
112945-52-5	Amorphous fumed silica	5% - 10%
64741-44-2	Distillates (petroleum), straight-run middle	5% - 10%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Comments Ingestion	Treat according to person's condition and specifics of exposure. No first aid should be needed.
-----------------------	--

Inhalation	Remove to fresh air. No first aid should be needed.
Skin Contact	Remove from skin and wash thoroughly with soap and water or waterless cleanser. Get medical attention if irritation or other ill effects develop or persist.
Eye Contact	Immediately flush with water for 15 minutes. Seek medical attention.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	N/A
Unsuitable Extinguishing Media	N/A
Auto-ignition Temperature	Not determined
Flammability Limits in Air	Not determined
Extinguishing Media	On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.
Special Fire Fighting Procedures	Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Unusual Fire or Explosion Hazards	None known

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release	Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.
---	--

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Section 7. Handling and Storage

Handling	Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container closed. Do not take internally. Use reasonable care.
Storage	Keep container closed and store in a cool, well ventilated area, away from water or moisture.

Other Precautions

Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control MEKO within the exposure guidelines or use respiratory protection.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	N/A	N/A	N/A
	Vinyl Oximino Silane	N/A	N/A	N/A
	Methyl Oximino Silane	N/A	N/A	N/A
	Dimethylpolysiloxane	N/A	N/A	N/A
	Amorphous fumed silica	10 mg/m3	6 mg/m3	N/A
	Distillates (petroleum), straight-run middle	N/A	N/A	N/A

Personal Protective Equipment

Goggles, Gloves

**Eye Protection
Skin Protection**

Safety goggles or glasses with side shields are recommended.
Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves:
Silver Shield® 4H®

**Respiratory protection
Precautionary Measures**

No respiratory protection should be needed with good local ventilation.
Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container closed. Do not take internally. Use reasonable care.

Comment

Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control methyl ethyl ketoxime within the exposure guidelines or use respiratory protection.

Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions.

Section 9. Physical and Chemical Properties
--

Physical State	Paste
Color	Grey
Odor	Slight
Odor Threshold	N/A
Solubility	Negligible in water
Partition coefficient Water/n-octanol	N/A
VOC%	2.8%
Viscosity	Not applicable
Specific Gravity	1.41

Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	Not Applicable
FP Method	N/A
Ph	Not applicable
Melting Point	Not applicable
Boiling Point	Not applicable
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	N/A
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not applicable
Vapor Density	Not applicable

Section 10. Stability and Reactivity

Materials to Avoid / Incompatibility	Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous vapors to form as described in Section 8.
Conditions to Avoid	None known
Hazardous polymerization	Will not occur
Chemical Stability	Stable

Section 11. Toxicological Information

Special Hazard Information on Component	Methyl Oximino Silane (22984-54-9) Possible skin sensitizer Vinyl Oximino Silane (2224-33-1) Possible skin sensitizer
---	--

Section 12. Ecological Information

Fate and Effects in Waste Water Treatment Plants	Complete information is not yet available.
Environmental Effects	Complete information is not yet available.
Environmental Fate and Distribution	Complete information is not yet available.

Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	N/A
DOT Classification	N/A
Packing Group	N/A
Air Shipment (IATA)	Not subject to IATA regulations.
Ocean Shipment (IMDG)	Not subject to IMDG code.
Road Shipment Information (DOT)	Not subject to DOT regulations.

Section 15. Regulatory Information

	The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.
TSCA Status	All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.
SARA Title III Section 302 Extremely Hazardous Substances	None
SARA Title III Section 304 CERCLA Substances dangereuses	None
SARA Title III Section 312 Hazard Class	Acute: Yes Chronic: No Fire: No Pressure: No Reactive: No
SARA Title III Section 313 Toxic Chemicals	None present or none present in regulated quantities.
California Proposition 65	This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known

Section 16. Other Information

Revision Date 5/28/2015

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.