



Safety Data Sheet

Dynatex® 49392 Grey GTX Multi-Seal

Section 1. Identification

Product Identifier Dynatex® 49392 Grey GTX Multi-Seal

Synonyms 49392GY10

Manufacturer Stock Numbers 49392GY10

Recommended use Refer to Technical Information

Uses advised against Refer to Technical Information

Manufacturer Contact

Address Dynatex a division of Soudal Accumetric
350 Ring Road
Elizabethtown, KY, 42701
USA

Phone
(270) 769-3385

Emergency Phone
(800) 424-9300
CHEMTREC

Fax
(270) 769-6418

Section 2. Hazards Identification

Classification EYE DAMAGE/IRRITATION - Category 2A
HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD - Category 3
HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD -
Category 3

SENSITIZATION - SKIN - Category 1

Signal Word Warning

Pictogram



Hazard Statements

Causes serious eye irritation
Harmful to aquatic life with long lasting effects
Harmful to aquatic life
May cause an allergic skin reaction

Precautionary Statements

Response

If eye irritation persists: Get medical advice/attention.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If medical advice is needed, have product container or label at hand.
If on skin: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.

Prevention

Avoid breathing dust/fume/gas/mist/ vapors/spray.
Avoid release to the environment
Contaminated work clothing must not be allowed out of the workplace.
Wash hands thoroughly after handling.
Wear eye protection/face protection.
Wear protective gloves.

Storage

N/A

Disposal

Dispose of contents/container in accordance with local, state and federal regulations.

Ingredients of unknown toxicity

0%

Hazards not Otherwise Classified

Additional Information

None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
1760-24-3	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	1% - 5%
77-58-7	Dibutyltin dilaurate	0.1% - 1%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Comments

Treat according to person's condition and specifics of exposure.

Ingestion	DO NOT INDUCE VOMITING. Seek immediate medical attention.
Inhalation	Remove to fresh air. If symptoms persist, obtain appropriate medical attention.
Skin Contact	Remove from skin and immediately flush with water for 15 minutes. Get medical attention if irritation or ill effects develop or persist.
Eye Contact	Immediately flush eyes with water for at least 15 minutes. Get medical attention if irritation develops.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.
Unsuitable Extinguishing Media	None known
Special Fire Fighting Procedures	Fire responders must wear self-contained breathing apparatus and full protective equipment. Move fire-exposed containers if it can be done without risk to firefighters. If possible, control water run-off to prevent environmental contamination.
Unusual Fire and Explosion Hazards	When involved in a fire, this material may decompose and produce the following toxic gases: carbon monoxide, carbon dioxide, nitrogen oxides, aldehydes, silicon dioxide, and various polymer compounds. Contact with water will release small quantities of flammable methanol.

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release	Observe all personal protective equipment recommendations as described in Section 8. Scrape all spilled materials for disposal. This material is not classified as a hazardous waste per 40 CFR 261. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable.
---	---

Section 7. Handling and Storage

Handling	Avoid breathing vapors in top of shipping container. Keep container closed. Use with adequate ventilation. Avoid contact with skin and clothing. Wash thoroughly after handling.
Storage	Keep container closed and store in a cool, well ventilated area, away from water or moisture.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure	Ingredient Name	ACGIH	OSHA	STEL
-----------------------	-----------------	-------	------	------

Limits	TLV	PEL	
N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	N/A	N/A	N/A
Dibutyltin dilaurate	N/A	N/A	N/A
Personal Protective Equipment	Goggles		
Eye Protection	Use proper protection - safety glasses as a minimum.		
Skin Protection	Wash at mealtimes and end of shift. If skin contact occurs, change contaminated clothing as soon as possible and thoroughly flush affected areas with cool water. Chemical protective gloves are recommended.		
Ventilation	Local exhaust ventilation is recommended to maintain vapor level below TLV.		
Respiratory Protection	Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.		
Note	These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions.		

Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Various
Odor	Slight
Odor Threshold	N/A
Solubility	Water dilutable in wet stage
Partition coefficient Water/n-octanol	N/A
VOC%	10 g/L
Viscosity	N/A
Specific Gravity	1.42
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	200C
FP Method	N/A
pH	N/A
Melting Point	Not determined
Boiling Point	Not determined
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not determined
Flammability	N/A

each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	Caulking & Glaziers, NOI
DOT Classification	None
Packing Group	None

Section 15. Regulatory Information

TSCA Status	All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.
SARA Title III Section 302 Extremely Hazardous Substances	None
SARA Titre III Section 304 CERCLA Substances dangereuses	None
SARA Title III Section 313 Toxic Chemicals	None present or none present in regulated quantities.
California Prop 65	WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer, and Diisodecyl phthalate, which is known to the State of California to cause birth defects and/or other reproductive harm. For more information, go to www.P65Warnings.ca.gov
Canada Domestic Substances List	All ingredients are listed on the DSL.

Section 16. Other Information

Revision Date 6/7/2018

Disclaimer
The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.