



Safety Data Sheet

Dynatex® 49433 Super Glue Gel

Section 1. Identification

Product Identifier Dynatex® 49433 Super Glue Gel

Synonyms 49433CL12

Manufacturer Stock Numbers 49433CL12

Recommended use Refer to Technical Information

Uses advised against Refer to Technical Information

Manufacturer Contact

Address

Dynatex a division of Soudal Accumetric
350 Ring Road
Elizabethtown, KY, 42701
USA

Phone

(270) 769-3385

Emergency Phone

(800) 424-9300

CHEMTREC

Fax

(270) 769-6418

Section 2. Hazards Identification

Classification

EYE DAMAGE/IRRITATION - Category 2A

FLAMMABLE LIQUIDS - Category 4

SKIN CORROSION/IRRITATION - Category 2

SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3

Signal Word

Warning

Pictogram



Hazard Statements

Causes serious eye irritation
Causes skin irritation
Combustible liquid
May cause respiratory irritation.

Precautionary Statements

Response

Call a poison center/doctor if you feel unwell.
If eye irritation persists: Get medical advice/attention.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If on skin: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use for extinction: CO2, powder or water spray.
Read label before use.
Take off contaminated clothing and wash it before reuse.

Prevention

Avoid breathing dust/fume/gas/mist/ vapors/spray.
Keep away from heat.
Use only outdoors or in a well-ventilated area.
Wash hands thoroughly after handling.
Wear eye protection/face protection.
Wear protective gloves.
Wear protective gloves/eye protection/face protection

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal

Dispose of contents/container in accordance with local, state and federal regulations.

Ingredients of unknown toxicity

0%

Hazards not Otherwise Classified

Additional Information

None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
7085-85-0	Ethyl-2-Cyanoacrylate	50% - 100%
123-31-9	Hydroquinone	0.1% - Max
26915-72-0	Methoxy Polyethylene Glycol 1000 Methacrylate	0.1% - 1%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Eye Contact	Flush with warm water. If eyelids are bonded closed, release eyelashes with warm water by covering the eye with a wet pad. Do not force eye open. See supplemental section for emergency action.
Skin Contact	Soak in warm water. Do not pull skin apart. See supplemental section for emergency action.
Inhalation	Remove to fresh air. If symptoms persist, obtain appropriate medical attention.
Ingestion	Ingestion is unlikely. See supplemental section for emergency action.
First Aid Supplement	Cyanoacrylate adhesive is a very fast setting and strong adhesive. It bonds to human tissue and skin in seconds. Experience has shown that accidents due to Cyanoacrylates are best handled by passive, non-surgical first aid. Treatment of specific types of accidents are suggested as follows:
Skin Contact	Remove excess adhesive. Soak in warm, soapy water. The adhesive will come loose from the skin in several hours. Dried adhesive does not present a health hazard even when bonded to the skin. Avoid contact with clothes, fabrics, rags, or tissue. Contact with these materials may cause polymerization. The polymerization of large amounts of adhesive will generate heat causing smoke, skin burns, and strong, irritating vapors. Wear rubber or polyethylene gloves and an apron when handling large amounts of adhesive.
Skin Adhesion	First immerse the bonded surfaces in warm, soapy water. Peel off or roll the surfaces open with the end of a blunt edge, such as a spatula or a spoon handle, then remove adhesive with soap and water. Do not try to pull the surfaces apart with a direct opposing action.
Eyelid adhesion	In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye will open without further action, typically in one to two days. There will be no residual damage. Do not try to pull the surfaces apart with a direct opposing action.
Adhesive in eye	Adhesive introduced into the eyes will attach itself to the eye protein and will disassociate from it over intermittent periods, usually several hours. This will cause periods of weeping until clearance is achieved. It is important to understand that disassociation will normally occur within a matter of hours, even with gross contamination.
Mouth	If lips are accidentally stuck together apply lots of warm water and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action. It is almost impossible to swallow cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in one to two days.
Burns	Cyanoacrylate gives off heat on solidification. In rare cases, large drops will increase in temperature enough to cause a burn. Burns should be treated normally after the lump of cyanoacrylate is released from the tissue as described above.
Surgery	It should never be necessary to use such drastic action to separate accidentally bonded skin.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Carbon Dioxide, Dry Chemical, Foam Use water fog to cool material in vicinity of fire.
Unsuitable Extinguishing Media	None known
Unusual Fire or Explosion Hazards	None known
Special Fire Fighting Procedures	Wear self- contained breathing apparatus.

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Observe all personal protection equipment recommendations. Do not use cloths for clean up. Flood spilled material with water to polymerize. Cured material can be scrapped up and disposed of as nonhazardous waste. Make sure spill area is well ventilated.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable.

Section 7. Handling and Storage

Storage	Store away from heat and direct sunlight to maximize shelf life. Store inside in a dry location. Keep container tightly closed.
Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapor or mist. Avoid contact with paper goods or fabric. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Ethyl-2-Cyanoacrylate	0.2 ppm	None	N/A
	Hydroquinone	2 mg/mm ³ A3	TWA 2 mg/mm ³	N/A
	Methoxy Polyethylene Glycol 1000 Methacrylate	N/A	N/A	N/A

Personal Protective Equipment	Goggles, Gloves
Eye Protection	Safety goggles or glasses with side shields are recommended.
Skin Protection	Polyethylene or non-reactive gloves. Do not use cotton, PVC or wool.

Ventilation

Local exhaust ventilation is recommended to maintain vapor level below TLV.

Respiratory Protection

Not applicable with good local exhaust. Use NIOSH approved respirator if there is a potential to exceed exposure limits.

Section 9. Physical and Chemical Properties

Physical State	Liquid
Color	Colorless
Odor	Characteristic
Odor Threshold	Not determined
Solubility	Not miscible in water
Partition coefficient Water/n-octanol	Not determined
VOC%	< 20 g/L (estimated)
Viscosity	Not determined
Specific Gravity	1.05
Density lbs/Gal	8.762
Pounds per Cubic Foot	N/A
Flash Point	87C 189F
FP Method	N/A
pH	Not determined
Melting Point	Undetermined
Boiling Point	>150C >302F
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not determined
Flammability	Not applicable
Decomposition Temperature	Not determined
Auto-ignition Temperature	Product is not self-igniting
Vapor Pressure	0.3 hPa @ 20C
Vapor Density	Not determined

Note

The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

Chemical stability	Stable under recommended storage conditions.
Hazardous Polymerization	Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.
Materials to Avoid / Incompatibility	Polymerized by contact with water, alcohols, amines, and alkalis.

Section 11. Toxicological Information

Special Hazard Information on Components	No known applicable information.
Component Toxicology Information	No known applicable information.

Section 12. Ecological Information

Fate and Effects in Waste Water Treatment Plants	Complete information is not yet available.
Environmental Effects	Complete information is not yet available.
Environmental Fate and Distribution	Complete information is not yet available.

Section 13. Disposal

Waste Disposal Method	<p>We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.</p> <p>This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.</p>
-----------------------	--

Section 14. Transport Information

UN Number	1993
UN Proper Shipping Name	Combustible liquid, NOS (more the 450 liters)
DOT Classification	Unrestricted under 450 liters
Packing Group	N/A
Air Shipment (IATA)	Proper Shipping Name: Aviation regulation liquids, n.o.s. (Cyanoacrylate ester) Hazard Class or Division: 9 Identification Number: UN3334 Packing Group: None

Ocean Shipment (IMDG)

Exceptions: Unrestricted under 500 mL
Proper Shipping Name: Unrestricted
Hazard Class or Division: None
Identification Number: None
Packing Group: None
Marine Pollutant: None

Section 15. Regulatory Information

TSCA Status

All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

SARA Title III Section 302
Extremely Hazardous
Substances

None

SARA Title III Section 304
CERCLA Substances
dangereuses

None

SARA Title III Section 312
Hazard Class

Acute: Yes
Chronic: Yes
Fire: Yes
Pressure: No
Reactive: Yes

SARA Title III Section 313
Toxic Chemicals

None present or none present in regulated quantities.

Massachusetts

No ingredient regulated by MA Right-to-Know Law present.

New Jersey

None known

Pennsylvania

None known

California Prop 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other reproductive harm.

Section 16. Other Information

Revision Date

6/6/2018

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.