



Safety Data Sheet

Dynatex® 52188 Belt Dressing

Section 1. Identification

Product Identifier Dynatex® 52188 Belt Dressing
Synonyms 52188CL10
Manufacturer Stock Numbers 52188CL10

Recommended use Refer to Technical Information
Uses advised against Refer to Technical Information

Manufacturer Contact
Address Dynatex a division of Soudal Accumetric
350 Ring Road
Elizabethtown, KY, 42701
USA

Phone
(270) 769-3385

Emergency Phone
(800) 424-9300
CHEMTREC

Fax
(270) 769-6418

Section 2. Hazards Identification

Classification ACUTE TOXICITY - ORAL - Category 5
EYE DAMAGE/IRRITATION - Category 2B
FLAMMABLE AEROSOLS - Category 3
SKIN CORROSION/IRRITATION - Category 3
SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3

Signal Word Warning

Pictogram



Hazard Statements	Causes eye irritation Causes mild skin irritation May be harmful if swallowed May cause drowsiness or dizziness Pressurized container; may burst if heated
Precautionary Statements	
Response	Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If inhaled: Remove person to fresh air and keep comfortable for breathing. If skin irritation occurs: Get medical advice/attention.
Prevention	Avoid breathing dust/fume/gas/mist/ vapors/spray. Keep away from heat. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local, state and federal regulations.

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

Additional Information None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
106-97-8	Butane	1% - 5%
74-98-6	Propane	1% - 5%
110-54-3	Hexane	10% - 20%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Eye Contact	Immediately flush with water for 15 minutes. Seek medical attention.
Skin Contact	Wash from skin with soap and water. If irritation persists, seek medical aid.
Inhalation	Remove victim to fresh air. Apply artificial respiration if needed. Get medical attention.
Ingestion	Drink large amounts of water and get medical attention. Do not induce vomiting unless directed by a physician.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Carbon Dioxide, Dry Chemical, Foam
Unsuitable Extinguishing Media	None known
Flammability (per flame projection)	Non-flammable
Flammable Limits in Air (Propellants)	Lower: N/A Upper: N/A
Special Fire Fighting Procedures	Keep containers cool using water spray. Use proper equipment to protect personnel from bursting containers.
Unusual Fire and Explosions Hazards	Contents under pressure. Do not expose to temperatures exceeding 120F as containers may vent, rupture or burst.

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release	Soak up spilled liquid with absorbent material. Place in closed metal drum for proper disposal.
---	---

Section 7. Handling and Storage

Handling	Contents under pressure. Use with adequate ventilation. Keep away from heat, sparks and open flames. Avoid contact eyes. Avoid prolonged or repeated contact with skin. Do not puncture or incinerate containers.
Storage	Do not store at temperatures above 120F. Keep out of reach of children. Store in a cool, dry, well-ventilated area away from incompatible materials. Store in accordance with NFPA 30B for Level 1 Aerosols.
Other Precautions	Read label precautions carefully. Follow label directions to avoid injury. Smoking in the area where this product is used should be strictly prohibited. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Butane	800 ppm	800 ppm TWA	N/A
	Propane	1000 ppm TWA	1000 ppm PEL	N/A
	Hexane	50 ppm	500 ppm	1000 ppm
Personal Protective Equipment	N/A			
Respiratory Protection	None required for normal use.			
Ventilation	Local Exhaust: Maintain adequate ventilation Mechanical (General): None required for normal use			

Skin Protection Chemical resistant gloves for pre-existing skin irritation and disorders.
 Eye Protection Safety glasses should be worn.
 Other Protective Clothing or Equipment Wash hands after use.

Section 9. Physical and Chemical Properties

Physical State	Aerosol spray
Color	White opaque viscous emulsion
Odor	Solvent
Odor Threshold	N/A
Solubility	Insoluble in water
Partition coefficient Water/n-octanol	N/A
VOC%	15.05%
Viscosity	Not established
Specific Gravity	0.95
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	>212F concentrate
FP Method	N/A
Ph	Not applicable
Melting Point	Not established
Boiling Point	Not established
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	< 1.00 (BuAc=1)
Flammability	Non-flammable (concentrate)
Decomposition Temperature	N/A
Auto-ignition Temperature	No established
Vapor Pressure	Not established
Vapor Density	N/A

Note The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

Chemical Stability	Stable
Hazardous polymerization	Will not occur
Conditions to Avoid	Open flames; Temperatures above 120F
Materials to Avoid	Strong oxidizers, strong alkalis, zinc, halogens, and acids
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide, ammonia vapors

Section 11. Toxicological Information

Carcinogenicity No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Section 12. Ecological Information

Fate and Effects in Waste Water Treatment Plants Complete information is not yet available.

Environmental Fate and Distribution Complete information is not yet available.

Environmental Effects Complete information is not yet available.

Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations, but contains SARA regulated substances. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Waste Disposal Methods Dispose of in accordance with local, state and federal regulations. Wrap container in newspaper and place in trash.

Section 14. Transport Information

UN Number 1950

UN Proper Shipping Name Aerosols, non-flammable

DOT Classification 2.2

Packing Group Not applicable

IATA UN Number UN1950

UN proper shipping name Aerosols, flammable (ACETONE, HEPTANE)

Transport Hazard Class(es) Class 2.1

Subsidiary risk ---

Label(s) 2.1

Packing group Not applicable

Environmental hazards No

Other information

IMDG

Passenger and cargo aircraft Allowed
Cargo aircraft only Allowed
UN Number UN1950
UN proper shipping name Aerosols, flammable (ACETONE, HEPTANE)
Transport Hazard Class(es)
Class 2.1
Subsidiary risk ---
Label(s) 2.1
Packing group Not applicable
Environmental hazards
Marine Pollutant Yes

Section 15. Regulatory Information

California Proposition 65

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.
This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:
None known

Section 16. Other Information

Revision Date

12/22/2015

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.