

### MUFFLER & TAILPIPE SEALANT PART NO. 49411

#### PHYSICAL PROPERTIES

|                        |                        |
|------------------------|------------------------|
| Physical Form .....    | Paste                  |
| Specific Gravity ..... | 1.9                    |
| Color .....            | Red                    |
| Odor .....             | Slight                 |
| Density lbs/Gal.....   | 15.85                  |
| Solubility .....       | Dilutable in wet stage |
| VOC % .....            | 0 grams/liter          |
| Percent Volatile ..... | 20                     |
| Viscosity .....        | 750,000 cPs            |



#### DESCRIPTION

*Dynatex® Muffler & Tailpipe Sealant* is a single component, non-slumping sealant that sets to form a hard surface. *Dynatex® Muffler & Tailpipe Sealant* serves to form a “gasket or seal against air infiltration”. Repairs holes and leaks in muffler, tailpipes and around joints. Makes new installations more secure.

#### FEATURES

- Easy to use
- Repairs leaks
- Waterproof
- Non-combustible
- Single component system, no mixing necessary
- Non-shrinking
- Easily applied sealant with water clean up capabilities

#### TYPICAL APPLICATIONS

- Mufflers, tailpipes, exhaust pipes and catalytic converters
- Seals connections in exhaust systems

#### TEMPERATURE RANGE

*Dynatex® Muffler & Tailpipe Sealant* freezes in the tube at temperatures below 32°F (0°C). The product can be warmed and applied at any temperature, but will not cure below 40°F (4°C). Freeze thaw cycles do not alter the cured product.

#### TYPICAL CURING PERFORMANCE

*Dynatex® Muffler & Tailpipe Sealant* cures by the evaporation of water and further cures with heat. Full cure will be affected after 24 hours of drying and driving at the maximum operating temperature.

## DIRECTIONS FOR USE

1. Surfaces to be repaired should be free of dirt, grease, oil and rust.
2. Wet the surface to be repaired with water.
3. Apply the sealer directly over the hole.
4. Allow to dry for 30 minutes, then start engine and allow to run for 10 more minutes.
5. For new installations, apply sealer around inside of larger pipe. Complete and seal the connection.

## STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **Dynatex® Muffler & Tailpipe Sealant** has a shelf life of 12 months from date of shipment.

In Countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

## TRANSPORTATION INFORMATION

### DOT Road Shipment Information

DOT (USA)..... Caulking Compound  
DOT Hazard Classification .....None  
UN/NA Number .....Not applicable  
Label Required .....None

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non-warranty:** Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

**Dynatex®** A division of Soudal Accumetric

**Dynatex**  
350 Ring Road  
Elizabethtown  
Kentucky 42701 USA  
(800) 999-2937  
TEL (270) 769-5557  
FAX (270) 769-6418  
*Outside U.S.*  
TEL +1(270) 769-5557  
FAX +1(270) 769-6418

**Accumetric Asia Pacific, LTD**  
18 Kitpanit Bldg. 5<sup>th</sup> Floor  
#502 Patpong Road  
Suriyawong, Bangrak  
Bangkok, 10500 Thailand  
TEL (662) 634-3060  
FAX (662) 634-3066

Email: [sales@dynatexinc.com](mailto:sales@dynatexinc.com)  
Website: [www.dynatexinc.com](http://www.dynatexinc.com)