

## TECHNICAL DATA SHEET

### CARB & CHOKE CLEANER PART NO. 52105

#### PHYSICAL PROPERTIES

Physical State.....	Aerosol
Color/Appearance.....	Clear liquid
Odor.....	Solvent odor
Specific Gravity.....	0.74
Boiling/Cond. Point.....	>100°F
Solubility.....	Insoluble in water
Evaporation Rate.....	>1.00 (BuAc=1)
Percent Volatile.....	44.8%
NFPA Flammability Rating.....	4*

\*Highly Flammable



#### DESCRIPTION

*Dynatex® Carb & Choke Cleaner* is a blend of solvents specifically formulated to dissolve and remove varnish, gum sludge and clean the residue deposited on carburetors and chokes during the normal operation of a motor vehicle or other gasoline engine powered equipment.

#### FEATURES

- Super jet spray cuts and removes grease and varnish
- Oxygen sensor safe
- Improves engine performance
- VOC Compliant
- Tested in accordance to 75/324/EEC Directive 6.1

#### TYPICAL APPLICATIONS

- Carburetors
- Manual and automatic chokes
- Linkages
- Heat risers
- PCV valves

#### DIRECTIONS FOR USE:

**GENERAL:** Shut off engine while spraying product. For pinpoint application, insert extension tube firmly into spray button. Hold can upright and press firmly on spray button to apply product. **If spray gets on paint or plastic, flush off immediately with water to avoid damage.**

**CARBURETORS, CHOKES & LINKAGES:** Remove air cleaner. Spray and flush exterior surface of carburetor and linkages, and allow to dry (approx. 30 minutes). When dry, start engine and spray short bursts into carburetor throat, flushing automatic choke valve and throttle (butterfly) plates. If engine stalls, stop spraying and restart it. Increase engine speed slightly until all liquid is drawn off, and then replace air cleaner.

**PCV VALVES:** Disconnect crankcase side of PCV valve. Insert extension tube into open end of valve unit and spray a small amount of product inside. Shake unit several times to make sure check valve is loose. Start engine and again spray into valve several times to completely flush it out. Reconnect PCV valve.

## GENERAL INFORMATION

This product is not recommended for use in pure oxygen environments and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet.

## STORAGE AND SHELF LIFE

*Dynatex® Carb & Choke Cleaner* should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building. Store in accordance with NFPA 30B for level 3 aerosols. *Dynatex® Carb & Choke Cleaner* has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

## TRANSPORTATION INFORMATION

### DOT Road Shipment Information

DOT Classification ..... Hazardous  
DOT Description Consumer Commodity ORM-D  
UN Number ..... UN1950  
Hazard Class ..... 2.2

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non-warranty:** Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

**Dynatex®** A division of Soudal Accumetric

### Dynatex

350 Ring Road  
Elizabethtown  
Kentucky 42701 USA  
(800) 999-2937  
TEL (270) 769-5557  
FAX (270) 769-6418

### Outside U.S.

TEL +1(270) 769-5557  
FAX +1(270) 769-6418

### Accumetric Asia Pacific, LTD

18 Kitpanit Bldg. 5<sup>th</sup> Floor  
#502 Patpong Road  
Suriyawong, Bangrak  
Bangkok, 10500 Thailand  
TEL (662) 634-3060  
FAX (662) 634-3066

Email: [sales@dynatexinc.com](mailto:sales@dynatexinc.com)  
Website: [www.dynatexinc.com](http://www.dynatexinc.com)