

### RUBBERIZED UNDERCOATING PART NO. 52175

#### PHYSICAL PROPERTIES

Physical State .....	Aerosol
Color/Appearance .....	Brown to black film
Odor .....	Alcohol
Specific Gravity .....	1.1
Boiling/Cond. Point .....	>0°F to 395°F
Melting/Freezing Point.....	Not applicable
Solubility .....	Not applicable
Evaporation Rate .....	Faster than ether
VOC % .....	39.11% (less water & exempt)
Percent Volatile .....	62% by volume
NFPA Flammability Rating.....	4*

\*Highly Flammable



#### DESCRIPTION

*Dynatex® Rubberized Undercoating* provides long-lasting rust and corrosion protection to the undercarriage of cars, truck, buses and trailers. Resilient rubber texture is tough and flexible with sound deadening qualities. Rubberized for maximum thickness, durability and flexibility.

#### FEATURES

- Seals and protects against rust and corrosion
- Quiets road noise
- Insulates
- Resists chipping
- Tested in accordance to 75/324/EEC Directive 6.1

#### TYPICAL APPLICATIONS

- Automotive frames and under-bodies
- Rocker panels
- Post preserving
- Gutters, roofs, drain systems
- Wheel wells
- Driveway cracks
- Rust holes

#### DIRECTIONS FOR USE:

1. Surface must be clean and dry before application.
2. Shake can vigorously until mixing balls break loose, and continue shaking for one minute.
3. Hold can 12-18 inches from surface and spray with smooth, short strokes.
4. Multiple coatings are effective. Allow 15 to 20 minutes between coats. Recommend a minimum of 2 coats.
5. After use, clear valve by turning upside down and spraying for a few seconds.
6. Remove any over-spray with kerosene or mineral spirits.

## GENERAL INFORMATION

This product is not recommended for use in pure oxygen environments and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet.

## STORAGE AND SHELF LIFE

*Dynatex® Rubberized Undercoating* should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse of storage building.

*Dynatex® Rubberized Undercoating* has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

## TRANSPORTATION INFORMATION

### DOT Road Shipment Information

DOT Classification ..... Hazardous  
DOT Description Consumer Commodity ORM-D  
UN Number ..... UN1950  
Hazard Class ..... 2  
Packing Group ..... N/A

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non-warranty:** Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

**Dynatex®** A division of SODAL Accumetric

**Dynatex**  
350 Ring Road  
Elizabethtown  
Kentucky 42701 USA  
(800) 999-2937  
TEL (270) 769-5557  
FAX (270) 769-6418  
*Outside U.S.*  
TEL +1(270) 769-5557  
FAX +1(270) 769-6418

**Accumetric Asia Pacific, LTD**  
18 Kitpanit Bldg. 5<sup>th</sup> Floor  
#502 Patpong Road  
Suriyawong, Bangrak  
Bangkok, 10500 Thailand  
TEL (662) 634-3060  
FAX (662) 634-3066

Email: [sales@dynatexinc.com](mailto:sales@dynatexinc.com)  
Website: [www.dynatexinc.com](http://www.dynatexinc.com)